



SPEAKERS




Standard 2-Way Speaker - Ceiling Mount
Frameless design, magnetic grill, Butyl rubber surround for improved bass performance

Code	Cone Woofer	Dome Tweeter	RMS Power (W)	Impedance	Frequency Response	Size (mm) (Ø x H)	Cutout (mm)	Weight (kg)
FLC-5E	5.25"	0.5"	35	8Ω	75Hz - 20kHz	Ø204 x 77	177	0,9
FLC-6E	6.5"	0.5"	40	8Ω	65Hz - 20kHz	Ø227 x 87	210	1,5
FLC-8E	8"	0.5"	50	8Ω	60Hz - 20kHz	Ø284 x 97	257	1,5




2-Way Speaker for PVA Systems - Ceiling Mount
Knob style 70V Transformer (Settings 15, 10, 5, 2.5W)

Code	Cone Woofer	Dome Tweeter	RMS Power (W)	Impedance	Frequency Response	Size (mm) (Ø x H)	Cutout (mm)	Weight (kg)
FLC-5E-KT	5,25"	0.5"	35	8Ω	75Hz - 20kHz	Ø204 x 77	177	1,15
FLC-6E-KT	6.5"	0.5"	50	8Ω	65Hz - 20kHz	Ø227 x 87	210	1,4
FLC-8E-KT	8"	0.5"	60	8Ω	60Hz - 20kHz	Ø284 x 97	257	1,7




Hanging Pendant 2-Way Speaker
Knob Style 70V Transformer (Settings 32, 16, 8, 4, 2W) for PA Systems
No cutting, no holes, high ceilings no problem

Code	Cone Woofer	Dome Tweeter	RMS Power (W)	Impedance	Frequency Response	Size (mm) (Ø x H)	Weight (kg)
PS-6	6.5"	0.75"	80	8Ω	45Hz - 20kHz	Ø308 x 365	4,3




Outdoor 2-Way Wall Speaker IP56
170° Swivel Aluminium Grill and Bracket for Longevity

Code	Cone Woofer	Dome Tweeter	RMS Power (W)	Impedance	Frequency Response	Size (mm) (W x D x H)	Weight (kg)
OWM-5E	5.25"	1"	60	8Ω	60Hz - 20kHz	190 x 256 x 225	2,5



Indoor 2-Way Wall Speaker
180° Swivel adjustment, Direct sound where you want it


Code	Cone Woofer	Dome Tweeter	RMS Power (W)	Impedance	Frequency Response	Size (mm) (W x D x H)	Weight (kg)
HYC-4	4"	0.5"	20	8Ω	90Hz - 18kHz	150 x 130 x 245	3,6
HYC-5	5.25"	0.5"	30	8Ω	75Hz - 18kHz	170 x 155 x 250	4,2
HYC-6	6.5"	1"	40	8Ω	70Hz - 20kHz	205 x 195 x 305	6,8



Garden Speaker 360° Sound IP56
Weather resistant ideal for Garden, Porch, Patio, Poolside.

Code	Cone Woofer	Dome Tweeter	RMS Power (W)	Impedance	Frequency Response	Size (mm) (Ø x H)	Weight (kg)
OGS-6	6.5"	1"	65	8Ω	55Hz - 20kHz	365 x 409	5

SPHERE CEILING SPEAKERS




White Plastic Sphere Ceiling Speakers

Code	Description	Watts RMS	Ohms	Input Line	Watts Adjustable
SPH-20	with 3m cable	20	8Ω	100V	2.5, 5, 10, 20
SPH-20WMT-W	with wall mount bracket	20	8Ω	70/100V	2.5, 5, 10, 20

These robust, yet elegantly attractive speakers are designed to give high quality sound reproduction and can be used in airports, churches, small theatres and other places of entertainment.

MEGAPHONE LOUDSPEAKERS



Megaphones

Code	Description	Watts RMS	Effective Distance	Power Source	Power Duration
GT-1225	Hand Grip / Shoulder Type	20	600m	10 x UM-2 (C) Dry Cell Batteries	± 7hrs
GT-125S	Hand Grip Type with Siren	20	600m	10 x UM-2 (C) Dry Cell Batteries	± 7hrs