

NEW

6KA CIRCUIT BREAKERS

Rated voltage: 240/415VAC
 Thermal Magnetic Release
 Rated Insulation Voltage Ui: 660V
 Rated Impulse Voltage Uimp: 4kV
 Integrated Lable Holder
 Accepts Pin / Fork Busbar
 Electrical and Mechanical life:
 <32A - 30 000 operations
 >32A - 10 000 operations
 Energy limiting class: ELC3
 Terminal Capacity: 35mm²
 Ambient working Temperature:
 -25°C to 55°C
60VDC capacity for 1P, 110VDC for 2P
 DIN Modules: 1M = 17,5mm



CSMB1C1X

CSMB2C1X



CSMB3C1X

6kA C-Curve Miniature Din Rail Circuit Breakers IP20 IEC60947-2 / VC8036

Amps	1 Pole Code 1M Wide	1P+N Code 2M Wide	2 Pole Code 2M Wide	3 Pole Code 3M Wide	4 Pole Code 4M Wide
1A	CSMBS1K1X	CSMBS1K1NX	CSMBS2K1X	CSMBS3K1X	CSMBS4K1X
2A	CSMBS1K2X	CSMBS1K2NX	CSMBS2K2X	CSMBS3K2X	CSMBS4K2X
3A	CSMBS1K3X	CSMBS1K3NX	CSMBS2K3X	CSMBS3K3X	CSMBS4K3X
4A	CSMBS1K4X	CSMBS1K4NX	CSMBS2K4X	CSMBS3K4X	CSMBS4K4X
5A	CSMBS1K5X	CSMBS1K5NX	CSMBS2K5X	CSMBS3K5X	CSMBS4K5X
6A	CSMBS1K6X	CSMBS1K6NX	CSMBS2K6X	CSMBS3K6X	CSMBS4K6X
10A	CSMBS1K10X	CSMBS1K10NX	CSMBS2K10X	CSMBS3K10X	CSMBS4K10X
16A	CSMBS1K16X	CSMBS1K16NX	CSMBS2K16X	CSMBS3K16X	CSMBS4K16X
20A	CSMBS1K20X	CSMBS1K20NX	CSMBS2K20X	CSMBS3K20X	CSMBS4K20X
25A	CSMBS1K25X	CSMBS1K25NX	CSMBS2K25X	CSMBS3K25X	CSMBS4K25X
32A	CSMBS1K32X	CSMBS1K32NX	CSMBS2K32X	CSMBS3K32X	CSMBS4K32X
40A	CSMBS1K40X	CSMBS1K40NX	CSMBS2K40X	CSMBS3K40X	CSMBS4K40X
50A	CSMBS1K50X	CSMBS1K50NX	CSMBS2K50X	CSMBS3K50X	CSMBS4K50X
63A	CSMBS1K63X	CSMBS1K63NX	CSMBS2K63X	CSMBS3K63X	CSMBS4K63X

6kA D-Curve Miniature Din Rail Circuit Breakers IP20 IEC60947-2 / VC8036

Amps	1 Pole Code 1M Wide	1P+N Code 2M Wide	2 Pole Code 2M Wide	3 Pole Code 3M Wide	4 Pole Code 4M Wide
6A	CSMBS1D6X	CSMBS1D6NX	CSMBS2D6X	CSMBS3D6X	CSMBS4D6X
10A	CSMBS1D10X	CSMBS1D10NX	CSMBS2D10X	CSMBS3D10X	CSMBS4D10X
16A	CSMBS1D16X	CSMBS1D16NX	CSMBS2D16X	CSMBS3D16X	CSMBS4D16X
20A	CSMBS1D20X	CSMBS1D20NX	CSMBS2D20X	CSMBS3D20X	CSMBS4D20X
25A	CSMBS1D25X	CSMBS1D25NX	CSMBS2D25X	CSMBS3D25X	CSMBS4D25X
32A	CSMBS1D32X	CSMBS1D32NX	CSMBS2D32X	CSMBS3D32X	CSMBS4D32X
40A	CSMBS1D40X	CSMBS1D40NX	CSMBS2D40X	CSMBS3D40X	CSMBS4D40X
50A	CSMBS1D50X	CSMBS1D50NX	CSMBS2D50X	CSMBS3D50X	CSMBS4D50X
63A	CSMBS1D63X	CSMBS1D63NX	CSMBS2D63X	CSMBS3D63X	CSMBS4D63X

Tripping Characteristic: AC
 Rated Voltage: 240V-2P / 415V-4P
 Rated Insulation Voltage: 660V
 Rated Impulse Voltage: 6kV
 Terminal Capacity: 25mm²
 Mechanical / Electrical Life:
 20000/10000 Operations



CSR2P25A300



CSR4P40A100

6kA Residual Current Circuit Breakers (Earth Leakage Relays) Without Overload VC8035

Amps	2 Pole Code 2M Wide 240V	Leakage Current	Amps	4 Pole Code 4M Wide 415V	Leakage Current
25A	CSR2P25A30	30mA	25A	CSR4P25A30	30mA
32A	CSR2P32A30	30mA	32A	CSR4P32A30	30mA
40A	CSR2P40A30	30mA	40A	CSR4P40A30	30mA
63A	CSR2P63A30	30mA	63A	CSR4P63A30	30mA
80A	CSR2P80A30	30mA	80A	CSR4P80A30	30mA
100A	CSR2P100A30	30mA	100A	CSR4P100A30	30mA
25A	CSR2P25A300	300mA	25A	CSR4P25A300	300mA
32A	CSR2P32A300	300mA	32A	CSR4P32A300	300mA
40A	CSR2P40A300	300mA	40A	CSR4P40A300	300mA
63A	CSR2P63A300	300mA	63A	CSR4P63A300	300mA
80A	CSR2P80A300	300mA	80A	CSR4P80A300	300mA
100A	CSR2P100A300	300mA	100A	CSR4P100A300	300mA