

STEEL DISTRIBUTION & METERING BOARDS



1600

Outdoor Distribution Kiosk IP55

- Manufactured to the latest standards.
- Pitched roof with sliding door. Insulators with 250A busbar included.
- Uni-strut cable termination. Standard - cable gland is optional
- Spare key **TDUV-04**.
- Unique lock and key, padlock option available.
- Hinged door option available.
- Finished in textured epoxy powder coat. Standard colours B22 Orange and RAL7032 Grey. Other colours manufactured to order.

3 CR12		Mild Steel		No. of Way	(mm) W x D
Orange	Grey	Orange	Grey		
DKS3	DKS3G	DKM3	DKM3G	3	250 x 250
DKS4	DKS4G	DKM4	DKM4G	4	250 x 250
DKS6	DKS6G	DKM6	DKM6G	6	250 x 250
DKS9	DKS9G	DKM9	DKM9G	9	250 x 250
DKS12	DKS12G	DKM12	DKM12G	12	460 x 250
DKS18	DKS18G	DKM18	DKM18G	18	460 x 250
DKS24	DKS24G	DKM24	DKM24G	24	460 x 250



1600

Outdoor Metering Kiosks IP55

3 CR12		Mild Steel		No. of (M) Single Phase	No. of (M) 3 Phase	(mm) W x D
Orange	Grey	Orange	Grey			
MKS3	MKS3G	MKM3	MKM3G	3	-	300 x 350
MKS6	MKS6G	MKM6	MKM6G	6	-	390 x 350
MKS9	MKS9G	MKM9	MKM9G	9	-	540 x 350
MKS12	MKS12G	MKM12	MKM12G	12	-	690 x 350
MKS18	MKS18G	MKM18	MKM18G	18	-	800 x 400
MKS24	MKS24G	MKM24	MKM24G	24	-	950 x 400
MKS6-3	MKS6-3G	MKM6-3	MKM6-3G	-	6	390 x 350
MKS12-3	MKS12-3G	MKM12-3	MKM12-3G	-	12	690 x 350

Features

- Pitched roof with 2 x sliding lid door (hinged doors optional extra)
- Polycarb reading windows (UV resistant)
- Insulators and busbars included (250A)
- Unique lock with key (padlockable optional)
- Spare key **TDUV-04**.
- Consumers Circuit Breakers can be mounted internally or be made accessible by a separate door



TDUV-04

MKM6



1600

1600

MKM6

FIBREGLASS METERING & DISTRIBUTION KIOSKS IP54

All Kiosks supplied with masonite chassis and gland plate



1 or 2 door type GLA/GLB

1 Door	2 Door	No. of Meter	Spare Mounting Board Masonite	Spare Gland Plate	Size (mm) H x W x D
GLA-2WG-*	GLB-2WG-*	2	ISK-2BB	GP-2B	1110 x 360 x 400
GLA-4WG-*	GLB-4WG-*	4	ISK-4BB	GP-4B	1110 x 530 x 400
GLA-6WG-*	GLB-6WG-*	6	ISK-6BB	GP-6B	1330 x 530 x 400
GLA-9WG-*	GLB-9WG-*	9	ISK 9BB	GP-9B	1330 x 700 x 400
GLA-12WG-*	GLB-12WG-*	12	ISK-12BB	GP-12B	1490 x 700 x 400
GLA-24WG-*	GLB-24WG-*	24	ISK-24BB	GP-24B	1490 x 880 x 400

*Add 'D' for Distribution or 'M' for Metering Kiosk

- All Kiosks include Busbar, Uni-strut and Busbar cover, masonite chassis and gland plate
- All Kiosks mounted on matching fibreglass plinth
- Manufactured to SABS 141
- Dimensions do not include plinth



No door type with lift off cover (shown below).



Shrouded Fibreglass Kiosks - No Door

Code	Description	H x W x D - Size (mm)
ISK-9WG-M	9 way metering kiosk	1000 x 580 x 390
ISK-15WG-D	15 way distribution kiosk	1000 x 580 x 390
ISK-15WG-M	15 way metering kiosk	1000 x 550 x 390
ISK-24WG-D	24 way distribution kiosk	1200 x 860 x 460
ISK-24MP	General Application kiosk	1340 x 980 x 550