

INSULATORS (1000V)

Polypropylene				Dough Moulded Compound (D.M.C)							
Insulators				Insulators				600V Transformer Bushings			
Type A, B, C	10mm	5mm	8mm	5mm	8mm	10mm	8mm	6mm (45A)	8mm (60A)	10mm (80A)	12mm (120A)
M/M	M10-MM-*	A5-MM-*	B8-MM-*	GL-5-*	GL-8-*	GL-10-*	VL-8-*	B6	B8	B10	B12
M/F	M10-MF-*	A5-MF-*	B8-MF-*	-	-	-	-	-	-	-	-
F/F	M10-FF-*	A5-FF-*	B8-FF-*	GP-5-*	GP-8-*	GP-10-*	VP-8-*	-	-	-	-

*Add colour to code: ● R (Red), ● BL (Blue), ● W (White), ● BK (Black). Eg. A5-MM-BL (Blue)

*Add colour to code: ● R (Red), ● BL (Blue), ● BK (Black).

Colour: Natural only.
Complete with gasket.
Brass Studs.

Dimensions: Polypropylene/DMC						Dimensions: D.M.C						Dimensions				
CAT No.	A mm	B mm	C mm	E mm	F mm	CAT No.	A mm	B mm	C mm	E mm	F mm	CAT No.	A mm	B mm	Cut Out mm	Stud
A5	25	16	25	20	-	G*-5	25	17	26	15	5	B6	85	28	15	M6
B8	41	22	40	25	-	G*-8	42	25	45	25	8	B8	95	30	21	M8
M8	40	32	45	-	8	G*-10	42	25	45	30	10	B10	110	33	22	M10
M10	40	32	45	-	10	V*-8	40	30	50	25	8	B12	120	35	24	M12

*Add L or P

D.M.C. Insulators					Dimensions									
					CAT No.	A mm	B mm	C mm	E mm	F mm				
10mm*	10mm*	12mm*	12mm*	16mm*	DJ10	50	40	45	30	10				
DJ10-MF-W	-	-	-	-	DF10	50	35	45	-	10				
-	DF10-FF-W	DF12-FF-W	DE12-FF-W	DD16-FF-W	DF12	50	35	45	-	12				
					DE12	60	45	60	-	12				
					DD16	60	45	60	-	16				

DMC = Dough Moulded Compound Max. 187°C
All Insulators manufactured with Brass inserts and bright Zinc-plated steel studs where applicable.

*Light Grey only

Trolley Line (D.M.C)		D.M.C with Flat Edge				
	Code SM1000 (Light Grey)		Code SM-35	Code SM-51	Code SM-76	
	Code SM1000-BK (Black)		Volt withstand	10kV	15kV	25kV
	Height 55mm		Screw	8mm	8mm	10mm
	Diameter 60mm		Dimension:			
	Hole/Stud 5/8" BSW		A	35mm	51mm	76mm
Code SM2000	Height 65mm	B	28mm	29mm	36mm	
Top Ø 50mm	Bottom Ø 72mm	C	32mm	36mm	50mm	
Hole M12		Available only in ● Red only				