



NATIONAL ADHESIVE DISTRIBUTORS (PTY) LTD

Reg No.: 2021/976762/07 VAT No.: 4370194633

Head Office:

Durban
93 Goodwood Road
Mahogany Ridge
Durban
South Africa

☎ +27 31 464 0273

Johannesburg

Unit 6, Hambleton Park
98 Richards Drive
Halfway House
Midrand, Johannesburg
South Africa

☎ +27 11 021 4177

Cape Town

Unit B19, Icon Park
Fourie Street
Brackenfell
Cape Town
South Africa

☎ +27 21 801 4258

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

PRODUCT NAME: **GLUEDEVIL SILICONE SEALER**

PRODUCT: SILICONE

2. COMPOSITION / INFORMATION ON INGREDIENTS:

>>PREPARATION

Chemical nature: Blend based on:

Crosslinker: silicalmethoxysiloxanes, amorphous silica and crosslinker.

Components presenting hazards Alkyltriacetoxysilanes (CAS: 4253-34-3 & 17689-77-9) :<5% - EEC classification: C – R34

Tributyltin Benzoate (CAS: 4342-36-3): 0.25% - EEC

Classification: T: R21-25-36/38-48/23/25.

C15-19 Alkane (CAS: 64742-46-7) :<25% - EEC

Classification Xn –R65

>>Further information during use, acetic acid is released (CAS: 64-19-7)

3. HAZARDS IDENTIFICATION:

MOST IMPORTANT HAZARDS

Adverse human health effects: Slightly irritating to eyes, respiratory system and skin.

Environmental effects: Presents no particular risk to the environment, provided the disposal requirements (see section 13) and national or local regulations are complied with.

Physical and chemical hazards

- Fire or explosion: Combustible.

-Further hazards: on contact with humidity: irritating vapours are released.

Classification / Specific hazards According to EEC criteria, this product is not classified as a “hazardous preparation”.

Further information after drying, may stick to the skin.



NATIONAL ADHESIVE DISTRIBUTORS (PTY) LTD

Reg No.: 2021/976762/07 VAT No.: 4370194633

Head Office:

Durban
93 Goodwood Road
Mahogany Ridge
Durban
South Africa

☎ +27 31 464 0273

Johannesburg

Unit 6, Hambleton Park
98 Richards Drive
Halfway House
Midrand, Johannesburg
South Africa

☎ +27 11 021 4177

Cape Town

Unit B19, Icon Park
Fourie Street
Brackenfell
Cape Town
South Africa

☎ +27 21 801 4258

4. FIRST –AID MEASURES:

Inhalation: Move to the fresh air. If irritation persists, consult a doctor.

Skin contact: Wipe off as much as possible (use a clean, soft, absorbent material). Wash immediately with plenty of soap and water.

Eye contact: Immediately rinse with water for a prolonged period whilst keeping the eyes wide open. If irritation persists, consult an eye specialist.

Ingestion: Consult a doctor if necessary.

5. FIRE – FIGHTING MEASURES:

Extinguishing media

-Suitable: Carbon dioxide (CO₂)

Foam.

Powders.

Water spray.

Not Suitable: None to our knowledge. If there is a fire close by, use suitable extinguishing agents.

Specific hazards: Combustible.

For further information, refer to section 10: "Stability and Reactivity".

Specific fire-fighting methods: Cool down the containers / equipment exposed to heat with a water spray.

Protection of fire fighters: Self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions: Avoid contact with skin and eyes. Do not breathe vapours.

Protective equipment: For further information refer to section 8 "Exposure-controls / personal protection". Mechanically ventilate the spillage area.

Environmental precautions: This product does not present any particular risk for the environment.

Methods for cleaning up:

-Recovery: Recover the product by scrapping with a spatula or a similar instrument.

Collect up the product and place it in a spare container:

- suitability: labelled.



NATIONAL ADHESIVE DISTRIBUTORS (PTY) LTD

Reg No.: 2021/976762/07 VAT No.: 4370194633

Head Office:

Durban
93 Goodwood Road
Mahogany Ridge
Durban
South Africa

☎ +27 31 464 0273

Johannesburg

Unit 6, Hambleton Park
98 Richards Drive
Halfway House
Midrand, Johannesburg
South Africa

☎ +27 11 021 4177

Cape Town

Unit B19, Icon Park
Fourie Street
Brackenfell
Cape Town
South Africa

☎ +27 21 801 4258

-tightly closed.

Neutralization: Absorb residues with:

-inert absorbent material.

-Cleaning / Decontamination: Decontaminate and wash the floor with:

-an appropriate solvent. (cf.: § 9) then wash with plenty of water.

-Disposal for disposal of solid materials refer to section 13 "Disposable considerations".

7. HANDLING AND STORAGE:

HANDLING

Technical measures Ventilation.

Measures: Do not exceed the occupational exposure limits (OEL).

Safe handling advice: Comply with instructions for use (refer to technical sheet).

Work outside or in a well-ventilated room.

STORAGE

Technical measures: Does not require any specific or particular technical measures.

Storage conditions

-Recommended: Keep:

-only in the original container

- the container tightly closed and dry.

Incompatible products: Strong oxidizing agents.

Packaging - Polyethylene liner in a metal drum varnished with epikote

Packaging materials

-Recommended: Polyethylene coated metals.

Further information: The product polymerises on contact with air.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION:

Engineering measures: Ensure good ventilation of the work station

Control parameters



NATIONAL ADHESIVE DISTRIBUTORS (PTY) LTD

Reg No.: 2021/976762/07 VAT No.: 4370194633

Head Office:

Durban
93 Goodwood Road
Mahogany Ridge
Durban
South Africa

☎ +27 31 464 0273

Johannesburg

Unit 6, Hambleton Park
98 Richards Drive
Halfway House
Midrand, Johannesburg
South Africa

☎ +27 11 021 4177

Cape Town

Unit B19, Icon Park
Fourie Street
Brackenfell
Cape Town
South Africa

☎ +27 21 801 4258

Occupational exposure limits

-limits (France): Acetic acid: VLE:25mg/m³ (10ppm)

-limits (U.S.A./ A.C.G.I.H.): Acetic acid: VLV (TWA) =25mg/m³ (10ppm)

Acetic acid: VLV (STEL) =37mg/m³ (15ppm)

Surveillance procedures Measure the concentration in the atmosphere. Personal protective equipment

-Respiratory protection: In the event of insufficient ventilation:

Respiratory protective device with a gas filter.

-Hand protection: Protective gloves made of rubber.

-Eye protection: Safety spectacles.

Collective emergency equipment: Eye fountain.

9. PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE

- Physical state: Thixotropic paste –Colour translucent or pigmented.

Odour: of vinegar. pH Not applicable

Specific temperatures

Decomposition temperature: > 200°C.

Flammability characteristics

-Flash point: >150°C (closed cup, according to method Afnor T 60103).

Oxidizing properties: Non oxidizing material according to EEC criteria.

Specific gravity

Approx. 1040 kg/m³ at 25°C

Solubility

-in water

Practically insoluble.

-in organic solvents

Insoluble in:

- acetone

-alcohol (ethanol)

Dispersible (partial solubilisation) in:

- petrol.

-white-spirit.



NATIONAL ADHESIVE DISTRIBUTORS (PTY) LTD

Reg No.: 2021/976762/07 VAT No.: 4370194633

Head Office:

Durban
93 Goodwood Road
Mahogany Ridge
Durban
South Africa

☎ +27 31 464 0273

Johannesburg

Unit 6, Hambleton Park
98 Richards Drive
Halfway House
Midrand, Johannesburg
South Africa

☎ +27 11 021 4177

Cape Town

Unit B19, Icon Park
Fourie Street
Brackenfell
Cape Town
South Africa

☎ +27 21 801 4258

- aromatic hydrocarbons (toluene, xylene).
- chlorinated solvents

10. STABILITY AND REACTIVITY:

Stability

Stable at room temperature provided it is not on contact with air.
Vulcanises at room temperature on contact with moisture in the air.

Hazardous reactions

-Conditions to avoid

No dangerous reactions known under normal conditions of use.
See technical data sheet.

- Hazardous decomposition products

During Vulcanisation, acetic acid is released.
(Quantity potentially released: <3% of product weight).

On combustion forms:

(Carbon oxides (CO + CO₂)).

Amorphous silica

11. TOXICOLOGICAL INFORMATION:

Acute toxicity

(Acetic acid).
LC 50 inhalation (Mouse) / 1h: 14 mg/l.
(Published data)

Local effects

Repeated or prolonged contact may cause slight irritation to the skin.
May cause slight temporary irritation to ocular mucous membranes.
No information available.

Sensitisation

Specific effects

-Mutagenicity

No information available.

Further information

At high concentrations, the vapours can be irritating to the respiratory system.

12. ECOLOGICAL INFORMATION:

MOBILITY

Precipitation

Slightly soluble product, readily forms deposits.

Expected behaviour of the product

Ultimate destination of the product: Soil and Sediment.

BIODEGRADABILITY

-Ultimate aerobic biodegradability

Not biodegradable

BIOACCUMULATION

Bioconcentration factor.

Not bioaccumulable.



NATIONAL ADHESIVE DISTRIBUTORS (PTY) LTD

Reg No.: 2021/976762/07 VAT No.: 4370194633

Head Office:

Durban
93 Goodwood Road
Mahogany Ridge
Durban
South Africa

☎ +27 31 464 0273

Johannesburg

Unit 6, Hambleton Park
98 Richards Drive
Halfway House
Midrand, Johannesburg
South Africa

☎ +27 11 021 4177

Cape Town

Unit B19, Icon Park
Fourie Street
Brackenfell
Cape Town
South Africa

☎ +27 21 801 4258

ECOTOXICITY

Effects on the aquatic environment

Acetic acid:

EC 50 (Daphnia: Daphnia magna) 24 h: 150 mg/l.

LC 50 (Fish: Pimephales promelas) / 96h: 88mg/l.

13. DISPOSAL CONSIDERATIONS:

WASTE FROM RESIDUES

Destruction / Disposal: Dispose of at a licensed waste collection point.

CONTAMINATED PACKAGING

Decontamination / cleaning: Separate the different packaging components and treat them separately:

Destruction / Disposal: Incinerate plastic packaging at a licensed installation.

Entrust the uncontaminated packaging to a licensed waste contractor.

Following decontamination, re-use or recycle metal packaging.

Disposable containers:

Incinerate at a licensed installation.

NOTE: The user's attention is drawn to the possible existence of local Regulations regarding disposal.

14. TRANSPORT INFORMATION:

INTERNAL REGULATIONS

Land

-Rail/road (RID/ADR): NOT restricted

Sea (IMO/IMDG): NOT restricted

Air (ICAO-IATA): NOT restricted

OTHER REGULATIONS

-France: Rail/road (RID/ADR): NOT restricted

NOTE

The above regulatory prescriptions are those valid on the date of Publication of this sheet.



NATIONAL ADHESIVE DISTRIBUTORS (PTY) LTD

Reg No.: 2021/976762/07 VAT No.: 4370194633

Head Office:

Durban
93 Goodwood Road
Mahogany Ridge
Durban
South Africa

☎ +27 31 464 0273

Johannesburg

Unit 6, Hambleton Park
98 Richards Drive
Halfway House
Midrand, Johannesburg
South Africa

☎ +27 11 021 4177

Cape Town

Unit B19, Icon Park
Fourie Street
Brackenfell
Cape Town
South Africa

☎ +27 21 801 4258

Given the possible evolution of transport regulations for hazardous Materials, it would be advisable to check their validity with your sales Office.

15. REGULATORY INFORMATION:

LABELLING

EEC regulations: Mandatory labelling (self-classification) of hazardous preparations:

NOT applicable.

NOTE: The regulatory information given above only indicates the principal)

Regulations specifically applicable to the product described in the Material Safety Data Sheet. The user's attention is drawn to the possible Existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or

Provisions.

16. OTHER INFORMATION:

Uses

-Recommended uses

Used for making joints, sealing and gluing.

(For further information, refer to the product technical data sheet).

-Prohibited uses: This product is only intended for industrial use.

- European inventory (EINECS, ELINCS): These polymers are not concerned by the EINC inventory.

The corresponding monomers are registered in the EINECS Inventory.

All the other constituents of this preparation are registered in the EINECS inventory.

-American inventory (TSCA): All the components of this preparation are registered in the TSCA inventory.

All the information of Material Safety Data Sheet is provided on the basis in good faith, and is believed to be trustworthy but is for reference only. National Adhesive Distributors (Pty) Ltd cannot accept any liability for the results whatsoever arising from the use of National Adhesive Distributors (Pty) Ltd products due that the utilization of these products is simply out of our control. The users are responsible for selecting the suitability of the products and methods of use.

DEC 2018