



Product Size	400ml
Gross Weight	358g
Net Weight	263g
UN Number	1950
Custom Code	3403.19.00
Country of Manufacture	RSA
Barcode	6001690300733
Article Number	030073

CHARACTERISTICS	
Colour	Clear
Texture	Liquid
Odour	Aromatic
Temp Range	<=35 °C

PACKAGING	
Type	Card Box
Dimensions	H:20 W:21 L:27cm
Box Weight	4.5kg
Packaging Group	Class II
Valve Type	360°
Cap	Translucent Blue
Pack Type	Aerosol
Units in Carton	12

Product Description

- ✓ **ANTI-STATIC LUBRICANT**
- ✓ **WATERPROOFS & INSULATES**
- ✓ **INHIBITS CORROSION**
- ✓ **PROTECTS**

Q-SILICONE SPRAY is a high-quality silicone spray that waterproofs and insulates electrical components, protects rubber and plastic components, inhibits rust and corrosion and is an anti-static lubricant.

Ideal Usage



Application of Product

Directions:

Shake well before use. Q-SILICONE SPRAY works best when the nozzle is pressed down firmly. Hold the can 25 cm away from area to be sprayed. Hold can in any position. Ensure that the surface to be sprayed is clean and dry. Use on electrical systems. Lubricates switchgears and prevents arcing. Prevents battery terminal corrosion. A non-staining lubricant for clips, hinges, rubber bushes and plastic fittings. Ideal for protecting vinyl and plastic surfaces.

Test Results/Approvals/Certificates

N/A

Safety Data Sheet Summary

Health/ Routes of entry

Threshold limit value: Hydrocarbon solvent lowest TVL(100ppm)

Symptoms of exposure

Inhalation May cause anesthesia, headache, dizziness, nausea and upper respiratory irritation

Skin contact: May cause drying of skin and/or irritation

Eye contact: May cause irritation, tears and redness

Ingestion: May cause irritation, nausea, vomiting and diarrhea

DANGER if swallowed can enter lungs and may cause chemical pneumonia.
Do not induce vomiting. Obtain medical assistance.