




WATERTIGHT JUNCTION BOXES

SCRWED LID - IP55


100x100 MS

TECHNICAL DATA SHEET

Directive	LVD 2014/35/EU	
Standards Amends	EN 60670-1:2005+A1:2013 Boxes and Enclosures, Electrical Installations EN 60670-22:2006 Boxes and Enclosures, Particular Requirements EN 60529 Degrees of Protection , Enclosures, IP Rate	
RoHS Compliant	2022/95/EC Restriction of Hazardous substances, RoHS	
Applications	Indoor – Outdoor - Residential – Industrial Plastic Junction box with Screwed Lid - INOX Screws Wiring, Junction or Extension With flexible Glands, entries for Accessories - Conduits - Cables	
Installations	Exposed – Wall mounted	
	Wiring, Power, Lighting, Automation, Telecom, CCTV, 	
Material	Polyvinyl Chloride > U-PVC	
Characteristics	IP Rate	Solid 5 Water 5
	Glow Wire Test	850 °C
	Resistance - UV	R
	Resistance - Chemicals	R
	Resistance - Fire	FR-SE
	Dielectric Strength	400V
	Temperature range	-15 °C +60 °C
	Color.1	Grey RAL7035



IP55



WATERTIGHT JUNCTION BOXES

SCRWED LID - IP55

100x100 MS



TYPE	100x100 MS/ G	100x100 MS/ W
CODE	32-21005-100	32-21023-100
A _mm	100	100
B / mm	50	50
D Pipe OD Ø _mm	16/20/25	16/20/25
E Entries Ø _mm	29	29
COLOR	Grey RAL7035	White RAL9010
PACKING / pcs	60	60

