




SERIES ALUPRES-Ex

CODE 460336EX



Datasheet

Specifications

Net Weight	4.725 KG
Rated current	63A
Frequency	50/60Hz
IP Protection degree	IP66
Poles	3P+ $\frac{1}{2}$
Clock Position	6h
Rated operating voltage	400V ●
Manufacturing material	Aluminum alloy
Width	125 mm
Execution	Wall mounting
Type of protection	Fuses
Insulation Class	I
Operating category	AC-23A / AC-3 63A - 415V
Dimensions	125X430X188 mm
Hole type	M32

Reference Standards and Directives

Certification and approval marks NYCE COLOMBIA, IECEx, EX, CE

Directives 2011/65/EU (RoHS), 2012/19/EU (WEEE), 2014/34/EU (ATEX), 2014/35/EU (LVD)

Reference Standards EN 50581:2012, EN 60079-0/A11:2013, EN 60079-0:2012, EN 60079-15:2010, EN 60079-31:2014, EN 60309-1:1999, EN 60309-1:1999/A1:2007, EN 60309-1:1999/A1AC:2014, EN 60309-2:1999, EN 60309-2:1999/A1:2007, EN 60309-2:1999/A2:2012, EN 60309-4:2007, EN 60309-4:2007/A1:2012, EN IEC 63000:2018

Atex characteristics

ATEX application zone	Zona/Zone 2, 21 and 22
Dust ATEX execution (Tmax1)	II 2D - Ex tb IIIC T70/T80 °C Db
Gas ATEX execution (Tmax1)	II 3G - Ex nR IIC T6 Gc

The images are purely indicative. Palazzoli reserves the right to make changes without notice.