

DPA M CLD RJ45B 48 (929 126)

- Ideally suited for retrofitting, protection of all lines
- For use in structured cabling systems according to class D up to 100 MHz
- Power over Ethernet IEEE 802.3 compliant (up to PoE++ / 4PPoE)
- For installation in conformity with the lightning protection zone concept at the boundaries from $O_B -2$ and higher






Figure without obligation



Basic circuit diagram DPA M CLD RJ45B 48



Dimension drawing DPA M CLD RJ45B 48

Universal arrester for Industrial Ethernet, Power over Ethernet (IEEE 802.3 compliant up to PoE++ / 4PPoE) and similar applications in structured cabling systems according to class D up to 100 MHz. Protection of all pairs by powerful gas discharge tubes. DIN rail mounted adapter type with sockets.

| Type Part No. | DPA M CLD RJ45B 48 929 126 |
|--|--------------------------------------|
| SPD class | TYPE 2 P2 |
| Nominal voltage (U_N) | 48 V |
| Max. continuous operating voltage (d.c.) (U_c) | 48 V |
| Max. continuous operating voltage (a.c.) (U_c) | 34 V |
| Max. continuous operating voltage (d.c.) pair-pair (PoE) (U_c) | 57 V |
| Nominal current (I_N) | 1 A |
| D1 Lightning impulse current (10/350 μ s) per line (I_{imp}) | 0.5 kA |
| C2 Nominal discharge current (8/20 μ s) line-line (I_n) | 1.25 kA |
| C2 Nominal discharge current (8/20 μ s) line-PG (I_n) | 2.5 kA |
| C2 Nominal discharge current (8/20 μ s) total (I_n) | 10 kA |
| C2 Nominal discharge current (8/20 μ s) pair-pair (PoE) (I_n) | 2.5 kA |
| Voltage protection level line-line for I_n C2 (U_p) | ≤ 700 V |
| Voltage protection level line-PG for I_n C2 (U_p) | ≤ 700 V |
| Voltage protection level line-line for I_n C2 (PoE) (U_p) | ≤ 900 V |
| Voltage protection level line-line at 1 kV/ μ s C3 (U_p) | ≤ 600 V |
| Voltage protection level line-PG at 1 kV/ μ s C3 (U_p) | ≤ 500 V |
| Voltage protection level pair-pair at 1 kV/ μ s C3 (PoE) (U_p) | ≤ 700 V |
| Cut-off frequency (f_c) | 100 MHz |
| Insertion loss at 100 MHz | ≤ 3 dB |
| Capacitance line-line (C) | ≤ 10 pF |
| Capacitance line-PG (C) | ≤ 10 pF |
| Operating temperature range (T_U) | -40 °C ... +80 °C |
| Degree of protection | IP 10 |
| For mounting on | 35 mm DINs rails acc. to EN 60715 |
| Connection (input / output) | RJ45 socket / RJ45 socket |
| Pinning | 1/2, 3/6, 4/5, 7/8 |
| Earthing via | 35 mm DINs rails acc. to EN 60715 |
| Enclosure material | zinc die-cast |
| Colour | bare surface |
| Test standards | IEC 61643-21 / EN 61643-21 / UL 497B |
| Approvals | UL, EAC |
| Weight | 96 g |
| Customs tariff number (Comb. Nomenclature EU) | 85366910 |
| GTIN | 4013364242258 |
| PU | 1 pc(s) |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.