

Data sheet

Operation method	Time setting
Output Operation	SIGNAL ON DELAY, SIGNAL OFF DELAY, SIGNAL ON-OFF DELAY, FLICKER, INTERVAL
Time operation	SIGNAL ON START
Terminal	11-pin plug
Power supply	100-240VAC~, 24-240VDC 
Setting range	0.05 to 0.5 sec, 0.1 to 1 sec, 0.5 to 5 sec, 1 to 10 sec, 0.05 to 0.5 min, 0.1 to 1 min, 0.5 to 5 min, 1 to 10 min, 0.05 to 0.5 hour, 0.1 to 1 hour, 0.5 to 5 hour, 1 to 10 hour, 5 to 50 hour, 10 to 100 hour
Signal Input Method	No-voltage input(NPN)
Control output	Time-limit SPDT (1c): 1, Instantaneous SPDT (1c): 1
Min. signal Width	INHIBIT, START, RESET: Approx. 50ms
Accessories	Bracket
Environment_Ambient temperature	-10 to 55°C, storage: -25 to 65°C
Environment_Ambient humidity	35 to 85%RH
Weight	Approx. 134.7g (approx. 87.5g)

※Sockets (8-pin sockets: PG-08, PS-08(N)/11-pin sockets: PG-11, PS-11(N)) are sold separately.

※Refer to time specifications for control time setting range by model.

※The weight includes packaging. The weight in parenthesis is for unit only.

※Environment resistance is rated at no freezing or condensation.