

Product SPECIFICATION SHEET

BOV-B, BUV-B



BOV-B



BOV-B






Specification

Rated load	Current / Voltage	A/VAC	10/300
Dielectric strength	Coil/Contact	V/S	2000
	Between contacts	V/S	2000
External connection wire		AWG/mm ²	20-14/0.5-2.5
Screw torque		Nm	0.8
Terminal protection degree			IP20

Matched relay

Socket model	Relay model	Metal Clip	Module	DIN clip
90.22	MK2P MK2PK	K-53		
	JQX10-2Z			
	60.2 70.2			
	AS80.2			
	AS2P-U			

Outline dimension, Wiring diagram



BOV-B



BOV-B






Specification

Rated load	Current / Voltage	A/VAC	10/300
Dielectric strength	Coil/Contact	V/S	2000
	Between contacts	V/S	2000
External connection wire		AWG/mm ²	20-14/0.5-2.5
Screw torque		Nm	0.8
Terminal protection degree			IP20

Matched relay

Socket model	Relay model	Metal Clip	Module	DIN clip
90.23	MK3P MK3PK	K-53		
	JQX10-3Z			
	60.3 70.3			
	AS80.3			
	AS3P-U			

Outline dimension, Wiring diagram



BRANCH CONTACT DETAILS

Johannesburg	010 202 3300
Germiston	011 418 9600
Cape Town	021 510 0710
Pinetown	031 700 4215
Riverhorse	031 492 4800

NATIONAL CALL CENTRE

Sales	010 202 3400
Technical	010 202 3500

www.acdc.co.za