



# FIRE DETECTION



# FIRE DETECTION SYSTEMS



*for a safer world!*

## ■ ADDRESSABLE FIRE DETECTION SYSTEM



**BSR-2104, BSR-2114**

### Addressable fire detection panel 2 or 4 loops/96 zones

- Produced in accordance with EN54-2, EN54-4
- 2 or 4 loops, 150 points per loop
- 32, 64 or 96 zone capability
- The programming of the panel can also be done using a PC
- Suitable for large installation such as malls, hotels, factories.

**BSR-2000**

Repeat panel for addressable fire detection panels BSR-2xxx.



**BSR-5032, BSR-5032/WP**

### Addressable siren with beacon

- 88 dB SPL
- IP 42 & IP65.

**BSR-5036/A, BSR-5036/A/WP**

### Addressable fire detection call point

- Waterproof version IP65 (WP).





## CONVENTIONAL FIRE DETECTION SYSTEMS



### BS-1619

#### The BS-1619 set contains:

- BS-1632 conventional fire detection control panel
- x2 A-920 batteries 12V/2.6Ah for the panel
- BS-655 smoke detector
- BS-660 heat of rise detector
- BS-536 manual call point
- BS-531 siren with beacon.

### BS-636

#### 6 zone fire detection panel

- Relay per zone
- Aux relay
- Programmable output for automatic answering machine.



VdS

IP30



### BS-1632,BS-1634,BS-1636

#### Fire detection panels with 2, 4 or 6 zones

- Compliance with the new CPR regulation
- Produced in accordance with EN 54-2, EN 54-4
- Alarm relay, fault relay, programmable auxiliary relay & 2 siren outputs.

### BS-1638,BS-1642,BS-1646

#### Fire detection panels with 8, 12 & 16 zones

- 8, 12 and 16 zone fire detection panels with identical operation and indications
- Programming and monitoring is done using a graphical display. Fully programmable depending on the requirements of each installation, providing detailed event information in Greek or English. They also have an events history memory
- All panels incorporate 2 outputs for sirens, an alarm relay, a fault relay and an auxiliary relay
- Ethernet control and programming capability (card GR-8530).



IP30

## CONVENTIONAL FIRE DETECTION SYSTEMS



EVPU

IP65

BS-536, BS-536/WP

### Manual call point

- Test-reset key
- Waterproof version IP65 (WP).

BS-655, BSR-6055/A

Conventional (BS-655) and addressable (BSR-6055/A) optical smoke detectors.



The company is certified by



Distributor



[www.olympia-electronics.gr](http://www.olympia-electronics.gr)

Tel. (+30) 23530 51200 | fax. (+30) 23530 51486 | info@olympia-electronics.gr

