

DIGITAL AC CLAMP METER

C-LOGIC 810



- ☐ Power Supply : 3×1.5V AAA Batteries
- ☐ Display 6000 counts
- ☐ Jaw Opening $\Phi 26\text{mm}/1.0''$
- ☐ Auto & Manual Ranging
- ☐ Auto Power Off
- ☐ Non-Contact Voltage Detector
- ☐ Diode Open Voltage 3.2V
- ☐ Continuity Buzzer $<50\Omega$
- ☐ Data Hold
- ☐ Display Backlight
- ☐ Work Light
- ☐ Low Battery Display
- ☐ Product Size :
218mm×78mm×35mm/8.9"×3.1"×1.4"
- ☐ Product Weight : 239g/0.53lb
- ☐ Certificate : RoHS
- ☐ Safety Rating : CAT III 600V



C-LOGIC 810

DIGITAL AC CLAMP METER

General	
Power Supply	3x1.5V AAA Batteries
Product Size	218mm×78mm×35mm
Product Weight	239g
Certificate	CE / ETL / RoHS
Safety Rating	CAT III 600V

Specs	
Display Counts	6000
Jaw Opening	Φ26mm/1.0"
Auto Ranging	✓
Auto Power Off	✓
Non-Contact Voltage Detector	✓
Open Volatge	1.5V
Continuity Buzzer	<60Ω
Data Hold	✓
Display Backlight	✓
Work Light	✓
Low Battery Display	✓

C-LOGIC 810

DIGITAL AC CLAMP METER

Specs	Range	Resolution	Accuracy
DC Voltage	600 mV/6/60 V	0,1 mV/0,001/0,01 V	$\pm(0,8\%+2)$
	600V	1V	$\pm(1\%+2)$
AC Voltage	600 mV/6/60 V	0,1 mV/0,001/0,01 V	$\pm(1\%+10)$
	600V	1V	$\pm(1,2\%+10)$
AC Current	6/60/600 A	0,001/0,01/0,1 A	$\pm(2,5\%+10)$
Resistance	600 Ω /6/60/600 K Ω /6 M Ω	0,1 Ω /0,001/0,01/0,1/1 K Ω	$\pm(1,2\%+2)$
	60M Ω	0,01 M Ω	$\pm(2\%+2)$
Capacitance	10/100/1000 nF	0,001/0,01/0,1 nF	$\pm(3\%+10)$
	10/100/1000 nF	1/10/100 nF	$\pm(3\%+10)$
	10/60 mF	10 μ F	$\pm(4\%+10)$
Frequency (A)	100 Hz/1 KHz	0,01/0,1 Hz	$\pm(1,5\%+5)$
Frequency (V)	100 Hz/1/10 KHz	0,01/0,1 Hz/0,001 KHz	$\pm(1,5\%+5)$
Frequency (Hz/Duty)	10/100 Hz/1/10 KHz	0,001/0,01/0,1 Hz/0,001 KHz	$\pm(0,5\%+5)$
	100 KHz/1/10 MHz	0,01/0,1 KHz/0,001 MHz	$\pm(0,5\%+5)$
Duty cycle	0,5-99 %	0,10%	$\pm(1,5\%+15)$
Temperature	-20-1000 $^{\circ}$ C	1 $^{\circ}$ C	$\pm(2\%+2)$
	-4-1832 $^{\circ}$ F	1 $^{\circ}$ F	$\pm(2\%+4)$

Product Code Information

SKU	CLOGIC810CBINT
EAN code	8435394775616
UPC code	810053671191
Pcs/export carton	20