

Specifications

DC Power supply, High stability, High efficiency, Dual indicating for V and I, CV, CC output, Current limiting and shorting protection

DC Power Supply:

1. parallel for doubling output current
2. In series for doubling output voltage
3. CC output :0-2A OR 3A OR 5A
4. MODEL: **DF1730SL2A,DF1730SL3A,DF1730SL5A,DF1740SL 6A,DF1750SL3A**
DF1760SL2A,DF1760SL3A,DF1760SL5A

	Voltage	Current	Inolication	Ripple	Source regulation	Load regulation
DF1730SC 2A,3A,5A	0-30V	0-2A,3A,5A	two meters	CV≤1mV CC≤3mV	CV≤1×10 ⁻⁴ CC≤2×10 ⁻³	CV≤1×10 ⁻⁴ CC≤2×10 ⁻³
DF1730SL 2A,3A,5A	0-30V	0-2A,3A,5A	two LEDs	CV≤1mV CC≤3mV	CV≤1×10 ⁻⁴ CC≤2×10 ⁻³	CV≤1×10 ⁻⁴ CC≤2×10 ⁻³
DF1730SB 2A,3A,5A	0-30V	0-2A,3A,5A	two LCDs	CV≤1mV CC≤3mV	CV≤1×10 ⁻⁴ CC≤2×10 ⁻³	CV≤1×10 ⁻⁴ CC≤2×10 ⁻³
DF1730SC 10A,20A	0-30V	0-10A 0-20A	two meters	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³
DF1730SL 10A,20A	0-30V	0-10A 0-20A	two LEDs	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³
DF1740SC6A	0-40V	0-6A	two meters	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³
DF1740SL6A	0-40V	0-6A	two LEDs	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³
DF1750SC3A	0-50V	0-3A	two meters	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³
DF1750SL3A	0-50V	0-3A	two LEDs	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³
DF1760SC 2A,3A,5A,10A	0-60V	0-2A,3A, 5A,10A	two meters	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³
DF1760SL 2A,3A,5A,10A	0-60V	0-2A,3A, 5A,10A	two LEDs	CV≤3mV CC≤10mV	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³	CV≤2×10 ⁻⁴ CC≤5×10 ⁻³