

DVPA120 DVPA200



**DV120PA
DV200PA**

MODEL	DV120PA	DV200PA
POWER OUTPUT	120W R.M.S	200W R.M.S
POWER SUPPLY	AC220V/1.5A DC12V/10A	AC220V/2.5A DC12V/15A
DISTORTION	LESS THAN 3% T.H.D. AT 1K Hz	LESS THAN 3% T.H.D. AT 1K Hz
INPUTS	MIC×3:10mV 10K OHM AUX×2:100mV 600 OHM	MIC×3:10mV 10K OHM AUX×2:100mV 600 OHM
S/N RATIO	-60dB	-60dB
FREQUENCY RESPONSE	40-15,000Hz ± 3dB AT 1W	40-15,000Hz ± 3dB AT 1W
TONE CONTROLS	TREBLE +9dB AT 10K Hz BASS +10dB AT 100Hz	TREBLE +10dB AT 10K Hz BASS +12dB AT 100Hz
OUTPUT IMPEDANCE	4Ω,8Ω,16Ω,100V	4Ω,8Ω,16Ω,100V
DIMENSION	440 (W) ×305 (D) ×130 (H) mm	440 (W) ×305 (D) ×130 (H) mm
NET WEIGHT	11.6KGS	14.4KGS