



Product SPECIFICATION SHEET



E560860 - E560900



- Modules provide flexibility to select distance between phases and supports
- Extremely robust construction
- Halogen free insulators
- RoHS compliant



Material: Steel, Glass Fibre Reinforced Polyamide,
Stainless Steel 304 (EN 1.4301)
Finish: Electrogalvanized
Max Working Voltage, IEC (Ui): 1 000 VAC, 1 500 VDC
Working Temperature: -40 to 130 °C
Complies With: IEC® 60439.1, IEC® 61439.1,
IEC® 60695-2-11 (Glow Wire Test 960 °C)
Flammability Rating: UL® 94V-0



Part Number	Article Number	Typical Application Current Rating	Busbars per Phase	Busbar Thickness	Busbar Width	Width W	Depth D	Unit Weight
ABS1-5MOD	560860	1 700 A Max	1	5 mm	50 – 125 mm	74 mm	67 mm	0,64 kg
ABS1-10MOD	560880	2 250 A Max	1	10 mm	50 – 125 mm	74 mm	67 mm	0,64 kg
ABS4-5MOD	560870	3 500 A Max	1 – 4	5 mm	50 – 125 mm	99 mm	67 mm	0,73 kg
ABS2-10MOD	560890	3 600 A Max	1 – 2	10 mm	50 – 125 mm	99 mm	67 mm	0,73 kg
ABS3-10MOD	560900	4 500 A Max	1 – 3	10 mm	50 – 125 mm	124 mm	67 mm	0,81 kg

BRANCH CONTACT DETAILS

Johannesburg 010 202 3300
Germiston 011 418 9600
Cape Town 021 510 0710
Pinetown 031 700 4215
Riverhorse 031 492 4800

NATIONAL CALL CENTRE

Sales 010 202 3400
Technical 010 202 3500
www.acdc.co.za