



# Product SPECIFICATION SHEET



E562800, E551060, E551010

## E562800



- Universal busbar support
- End cover available to prevent busbar from sliding out of position
- Clips available to accommodate multiple busbar widths
- RoHS compliant

Max Working Voltage, IEC (Ui): 1 000 VAC, 1 500 VDC

Working Temperature: -15 to 140 °C

Typical Application Current Rating: 630 – 1 200 A



Complies With: IEC® 61439.1

Flammability Rating: UL® 94V-0

| Part Number | Article Number | Busbars per Phase | Busbar Width (mm) | Busbar Thickness (mm) | D (mm) | H (mm) | W (mm) | A (mm) | B (mm) | C (mm) | Unit Weight (kg) |
|-------------|----------------|-------------------|-------------------|-----------------------|--------|--------|--------|--------|--------|--------|------------------|
| CFBS100T    | 562800         | 1                 | 60                | 10                    | 61     | 70     | 320    | 275    | 22     | 100    | 0,436            |

## E551060

## E551010



- Universal fixing system
- Installs quickly and easily
- Extremely robust construction
- Adjustable arms for easy mounting
- Halogen free insulators

Material: Steel, Glass Fibre Reinforced Polyamide  
 Max Working Voltage, IEC (Ui): 1 000 VAC, 1 500 VDC  
 Working Temperature: -40 to 130 °C  
 Complies With: IEC® 60439.1, IEC® 61439.1,  
 IEC® 60695-2-11 (Glow Wire Test 960 °C)  
 Flammability Rating: UL® 94V-0

| Part Number                                 | Article Number | Busbars per Phase | Busbar Width (mm) | Busbar Thickness (mm) | W (mm)    | A (mm)    | B (mm) | C (mm) | D (mm) |
|---------------------------------------------|----------------|-------------------|-------------------|-----------------------|-----------|-----------|--------|--------|--------|
| Typical Application Current Rating: 2 250 A |                |                   |                   |                       |           |           |        |        |        |
| UBS1-10TN                                   | 551060         | 1                 | 30 – 120          | 10                    | 380 – 610 | 360 – 590 | 176    | 300    | 70     |
| Typical Application Current Rating: 3 500 A |                |                   |                   |                       |           |           |        |        |        |
| UBS4-5TN                                    | 551010         | 1 – 4             | 30 – 125          | 5                     | 585 – 895 | 560 – 865 | 281    | 480    | 110    |

### BRANCH CONTACT DETAILS

Johannesburg 010 202 3300  
 Germiston 011 418 9600  
 Cape Town 021 510 0710  
 Pinetown 031 700 4215  
 Riverhorse 031 492 4800

### NATIONAL CALL CENTRE

Sales 010 202 3400  
 Technical 010 202 3500  
[www.acdc.co.za](http://www.acdc.co.za)