

Model: **EM4807**

- GS Marking -



GS marking, GS certification, GS approval, European directive and standards

[2008 NEW PRODUCT CATALOG][Page 17]

CE

The compact EM4807 moisture meter is very user-friendly. It can be used to measure the moisture level in sawn timber (also cardboard, paper) and hardened materials (plaster, concrete and mortar). It displays the moisture level in the material straightaway. In addition, The instrument can measure the ambient temperature.



Top of the Probe Cove

TESTING THE INSTRUMENT

There are two pairs of metal contacts on the top of the probe cover, they can be used test the instrument.

ENVIRONMENT TEMPERATURE MEASUREMENT

The current environment temperature is shown on the display.

Pressing and holding down the test button for about 3 seconds switches the instrument between celsius degree and fahrenheit degree measurements

BELT CLIP

Compact and Light weight, one hand operation, Rugged plastic case with belt clip for easy portability

LCD DISPLAY

Dual measurement scale large LCD display



ILLUMINATION

Including a built-in flashlight for illuminating an area at which said flashlight is directed.



Drive the probes into the wood or material to be measured, the indication bars indicates the reading.

Range of wood: 6~44%

Range of building material: 0.2~2.0%

Environment Temperature : 0~40°C / 32~104°F

Size: 145 x 44 x 34mm

Weight: about 132g (including batteries)

Battery: 1.5V, AAA or equivalent, 4 pieces

0