Receiver-transmitters

RTX200/433868

Serial BUS RS485 Connection

ASYNC @WL · TX BDI RX · ABS BOX

Compatible systems.: TP8-28 - TP8-28 GSM - TP10-42 - TP8-88 - TP20-440

Bidirectional receiver-transmitter module - Dual-band frequency 433MHz/868MHz - ASYNC@WL protocol - Manages uni and bidirectional communication with wireless devices of Tecnoalarm (number depending on the system) - Connection via RS485 serial bus - ABS casing - Design by Pininfarina - Dimensions (L x H x D) 270 x 156 x 68mm - White color

Item no. F102RTX200

Receivers

RX300/433868

ASYNC @WL · ABS BOX

Compatible systems: TP4-20 - TP4-20 GSM - TP8-28 - TP8-28 GSM - TP10-42 - TP8-88 - TP20-440

Receiver module - Dual-band frequency 433MHz/868MHz - ASYNC@WL protocol - Manages unidirectional communication with wireless devices of Tecnoalarm (number depending on the system) - Connection via RS485 serial bus - ABS casing - Design by Pininfarina - Dimensions (L x H x D) 270 x 156 x 68mm - White color

Item no. F102RX300

Control units

LCD300 WL

ASYNC @WL · TX BDI RX · LITHIUM BATTERY · 1 INPUT · 8 PROGRAMS MANAGED

Bidirectional console - Dual-band frequency 433MHz/868MHz - ASYNC@WL protocol - Manages max. 8 programs - 2x16 digits backlit LCD - NC input - Lithium battery (included) - Surface mounting - ABS casing - Design by Pininfarina - Dimensions (L x H x D) 120 x 175 x 46mm - White color
N.B. Compatible with receiver-transmitter RTX200/433868 only

Item no. F102LCD300WL

TX240

ASYNC @WL · 433 OR 868 MHz · LITHIUM BATTERY · PROGRAMS MANAGED · REMOTE CONTROL MANAGEMENT

Hand-held transmitter with 3 programmable function keys - Available with either 433MHz or 868MHz frequency band - ASYNC@WL protocol - Lithium battery (included) - ABS casing - Dimensions (L x H x D) 65 x 40 x 15.5mm

TX240-3/433	**Item no. F102TX240-3/433** 433MHz frequency band
TX240-3/868	**Item no. F102TX240-3/868** 868MHz frequency band

TX140 SOS

ASYNC @WL · 433 MHz · LITHIUM BATTERY · SOS

Emergency call button for home medical emergencies - 433MHz frequency band - Actuation either through push-button, embedded in the front side of the casing, or pull-switch, connected to the cord - ASYNC@WL protocol - Lithium battery (included) - ABS casing - Dimensions (L x H x D) 45 x 75 x 20

Item no. F102TX140