

# Product SPECIFICATION SHEET

## 230VAC, 600W, IMPACT DRILL, CHUCK 1.5-13MM

### GSB-13-RE



**A breakthrough that sets new standards, increased performance, better efficiency**

- Robust pot gear housing and clamp shell motor housing for tough jobsite conditions
- Powerful 650 W motor to suit versatile professional needs
- Compact ergonomic design for fatigue-free usage

#### TECHNICAL DATA

Rated input power	650W
Weight	2 Kg
No-load speed, 1st gear	0 rpm
Power Output	301W
Impact rate at no-load speed	0 - bpm
Rated torque	1.8 Nm
Drill spindle connecting thread	1/2"-20 UNF
Chuck capacity min/max	1.3 - 13mm
Drilling diameter in wood	25 /20 mm
Drilling diameter in concrete	13 mm
Drilling diameter in steel	10 / 10 mm
Drilling diameter in masonry	15 mm

#### TECHNICAL DATA

Total Vibration values (drilling in metal)	
Vibration emission value ah	3 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>
Total Vibration values (Impact drilling in concrete)	
Vibration emission value ah	26 m/s <sup>2</sup>
Uncertainty K	3 m/s <sup>2</sup>
Total Vibration values (screwdriving)	
Vibration emission value ah	2.5 m/s <sup>2</sup>
Uncertainty K	1.5 m/s <sup>2</sup>
Noise / vibration information	
Sound Pressure Level	97 dB (A)
Sound power level	108 dB (A)
Uncertainty K	5 dB

#### BRANCH CONTACT DETAILS

Johannesburg	010 202 3300
Germiston	011 418 9600
Cape Town	021 510 0710
Pinetown	031 700 4215
Riverhorse	031 492 4800

#### NATIONAL CALL CENTRE

Sales	010 202 3400
Technical	010 202 3500

[www.acdc.co.za](http://www.acdc.co.za)