Product Data Sheet

GW66208N

67 IB Range

Industrial-type socket-outlets conforming to IEC 309 Standard, with mechanical interlock consisting of a circuit breaker enabling the plug to be connected and disconnected only in the open position, and the switch to close only with the plug inserted. Wide range including models with rotary switch and fuseholder base, AUTOMATIKA with 6kA C characteristic miniature circuit breaker, and version with safety transformer. High application versatility thanks to the possibility of assembly in back-mounting and flush-mounting boxes, and boards of the 68 Q-DIN and Q-MC ranges.

Colour	Red	**Rated current (A)**	16
IP degree	IP67	**No. of poles**	3P+E
Shock resistance	IK08	**Reference h**	6
Type	Vertical	**Rated voltage**	380 - 415 V
Frequency	50/60 Hz	**Protection**	NO (SBF)
With back-mounting box	Yes	**Operating temperature**	-25 +40 °C
Electrocod	2222	**Glow wire test**	850 °C (IB socket) - 650 °C (bottom)
Thermo-pressure with ball	125 °C (IB socket) - 80 °C (bottom)		

BEHAVIOUR WITH CHEMICAL AND ATMOSPHERIC AGENTS

Saline solution	Acids		Bases		Solvents				Mineral oil	UV rays
	Concentrated	Diluited	Concentrated	Diluited	Hexane	Benzol	Acetone	Alcohol		
Resistant	Not resistant	Limited resistance	Limited resistance	Limited resistance	Limited resistance	Not resistant	Not resistant	Limited resistance	Limited resistance	Resistant

DIMENSIONAL



TECHNICAL SYMBOLOGY


IP67

IK08

850 °C (IB socket) - 650 °C (bottom)

125 °C (IB socket) - 80 °C (bottom)

STANDARDS/APPROVALS

GEWISS S.p.A. Via A. Volta, 1
24069 Cenate Sotto - Bergamo - Italy
tel. +39 035 94 61 11 fax +39 035 94 69 09

www.gewiss.com
sat@gewiss.com
Last update 17/02/2017

Data, measures, designs and pictures are shown only as informativ purposes, and could be changed without previous notice