

# KEM 325 YR M2ABS \*

## KEM ABS 10-80A

- IP65
- Recommended for indoor installation only
- Padlockable with three locks
- Door interlock with defeat mechanism
- Excellent insulating properties
- Good resistance against many chemicals
- Tested according to IEC 60947-3
- Katko uses recycled ABS plastic. Minor variance in properties of the material.
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here.**

## KEM 16-40 A Installation video guide

>>

## KEM 63-80 A Installation video guide

>>

## Technical datasheet >>

Accessories



Data subject to change without notice. Always confirm the data is correct from the seller.

## Product details

<b>SKU</b>	KEM 325 YR M2ABS *
<b>AC-21 400/415 V (A)</b>	40 A
<b>AC-21 690 V (A)</b>	40 A
<b>AC-22 400/415 V (A)</b>	25 A
<b>AC-22 690 V (A)</b>	25 A
<b>AC-23 400/415 V (A/kW)</b>	25 A / 11 kW
<b>AC-23 690 V (A/kW)</b>	25 A / 22 kW
<b>Cable Area to Switch Terminal (only Cu) (mm<sup>2</sup>) / Bolt size</b>	1.5-16
<b>EAN</b>	6419410277201
<b>Enclosure</b>	M2
<b>IP Rating</b>	IP66
<b>Number of Poles</b>	3
<b>Operation</b>	Front-operated
<b>Switch type</b>	Load Break Switch
<b>Weight (kg)</b>	0.4

## Dimensional drawing

