



KEM 325 YR M2 *

KEM Polycarbonate 10-630A

- IP66; Enclosure types M2, M3, M4, MF11, MF01, MF02 MF03, MF04
- Self-extinguishing material
- Wide operating temperature range
- Padlockable with 3 locks
- Door interlock with defeat mechanism
- Excellent insulating properties
- Good UV resistance
- Good resistance against many chemicals
- Tested according to IEC 60947-3
- **Note!** Al-cables cannot be connected directly to switch terminals. For Al-cable connection please use a bi-metal cable connector, **available here.**

KEM 16-40 A Installation guide video
>>

KEM 63-80 A Installation guide video
>>

Technical datasheet >>

Accessories

Data subject to change without notice. Always confirm the data is correct from the seller.

Product details

SKU	KEM 325 YR M2 *
AC-21 400/415 V (A)	40 A
AC-21 690 V (A)	40 A
AC-22 400/415 V (A)	25 A
AC-22 690 V (A)	25 A
AC-23 400/415 V (A/kW)	25 A / 11 kW
AC-23 690 V (A/kW)	25 A / 22 kW
Cable Area to Switch Terminal (only Cu) (mm²) / Bolt size	1.5-16
EAN	6419410444603
Enclosure	M2
IP Rating	IP66
Number of Poles	3
Operation	Front-operated
Switch type	Load Break Switch
Weight (kg)	0.4

Dimensional drawing

