

Product SPECIFICATION SHEET



LS---EU SERIES

Overview

LandStar E series is reliable, stable, and economical solar charge controller, easy for operation. Based on the LS-E series, LS-EU series add a +5V/1.2A USB terminal output which can charge mobile phone, or power DC fans, and other DC electronic device.



Features

- 3-Stage intelligent PWM charging: Bulk, Boost/Equalize, Float
- Support 3 charging options: Sealed, Gel, and Flooded
- Battery status LED indicator can indicate battery situation
- Battery temperature compensation function
- With humanized settings, operation will be more comfortable and convenient
- The USB will provide power supply that can charge for electronic equipment (LS EU series only)
- Battery type and load output can be set via button
- Extensive Electronic protection



Solar Car




Solar Home



Solar Backpack



Solar Boat



Solar Street Light



Solar Power Generator

BRANCH CONTACT DETAILS

Johannesburg	010 202 3300
Germiston	011 418 9600
Cape Town	021 510 0710
Pinetown	031 700 4215
Riverhorse	031 492 4800

NATIONAL CALL CENTRE

Sales	010 202 3400
Technical	010 202 3500

www.acdc.co.za

Product SPECIFICATION SHEET



LS---EU SERIES

Model	LS0512 EU	LS1012 EU	LS1024 EU	LS2024 EU	LS3024 EU
Nominal system voltage	12VDC		12/24VDC Auto		
Rated charge current	5A	10A		20A	30A
Rated discharge current	5A	10A		20A	30A
Battery input voltage range	8V ~ 16V		8V ~ 32V		
Max. PV open circuit voltage	30V		50V		
Self-consumption	12V≤5mA; 24V≤7mA				
Charge Circuit Voltage Drop	≤0.13V				
Discharge Circuit Voltage Drop	≤0.17V				
USB input interface	5VDC/1.2A				5VDC/2A
Temperature compensation coefficient	-5mV/°C/2V				
Working environment temperature	-35°C ~ +55°C				
Humidity	≤95%,(N.C.)				
Enclosure	IP20				
Grounding	Common Positive				
Overall dimension	109.7x65.5 x20.8mm	120.3x67 x21.8mm	120.3x67 x21.8mm	148x85.6 x34.8mm	148x106.8 X43.7mm
Mounting dimension	100.9mm	111.5mm		138mm	
Mounting hole size	φ4.5				
Terminals mm ²	14AWG/2.5	12AWG/4	12AWG/4	10AWG/6	8AWG/10
Net weight	0.09kg	0.10kg	0.10kg	0.18kg	0.29kg

BRANCH CONTACT DETAILS

Johannesburg 010 202 3300
 Germiston 011 418 9600
 Cape Town 021 510 0710
 Pinetown 031 700 4215
 Riverhorse 031 492 4800

NATIONAL CALL CENTRE

Sales 010 202 3400
 Technical 010 202 3500

www.acdc.co.za