



Product SPECIFICATION SHEET



MN1 Series





GENERAL

CT TYPE	RING TYPE
INPUT CURRENT	0A – 10A MIN 0A – 300A MAX
OUTPUT CURRENT	4mA – 20mA
SYSTEM VOLTAGE	660V AC
FREQUENCY	50Hz
STANDARD	IEC/SANS 61869-2

CASING

MATERIAL	MOULDED ABS
TERMINAL COVER	YES
MOUNTING TYPE	DINRAIL / CHASSIS
INNER DIAMETER	32mm

MN2 Series



GENERAL

CT TYPE	RING TYPE
INPUT CURRENT	0A – 20A MIN 0A – 750A MAX
OUTPUT CURRENT	4mA – 20mA
SYSTEM VOLTAGE	660V AC
FREQUENCY	50Hz
STANDARD	IEC/SANS 61869-2

CASING

MATERIAL	MOULDED ABS
TERMINAL COVER	YES
MOUNTING TYPE	DINRAIL / CHASSIS
INNER DIAMETER	38mm ID 40mm BUSBAR

BRANCH CONTACT DETAILS

Johannesburg	010 202 3300
Germiston	011 418 9600
Cape Town	021 510 0710
Pinetown	031 700 4215
Riverhorse	031 492 4800

NATIONAL CALL CENTRE

Sales	010 202 3400
Technical	010 202 3500
www.acdc.co.za	