

DIGITAL THERMOMETER

MS6511/MS6512

Features:

- ▶ Large LCD Display
- ▶ Resolution: 0.1°C, 0.1°F, 0.1K
- ▶ Built-In Ambient Temperature Compensation
- ▶ Auto Power Off
- ▶ MAX/MIN/AVG and Data Hold

Specifications

	MS6511	MS6512
Specifications		
Thermocouple Type	K, J, T, E	K, J, T, E
Channel	Single	Dual
Measurement Range	K	-200.0°C to +1372°C / -328.0°F to +2501°F
	J	-210.0°C to +1200°C / -346.0°F to +2192°F
	T	-250.0°C to +400°C / -418.0°F to +752°F
	E	-150.0°C to +1000°C / -238.0°F to +1832°F
	R	0°C to +1767°C / 32°F to +3212°F
S	0°C to +1767°C / 32°F to +3212°F	
N	-200.0°C to +1300°C / -328.0°F to +2372°F	
Resolution	0.1°C, 0.1°F, 0.1K	
Accuracy	±(0.5% + 0.5°C)	
Ambient Temperature Compensation	●	
Auto Power Off	●	
MAX/MIN/AVG	●	
DATA Hold	●	
General		
Power Supply	1x9V 6F22 Battery	
Product Size	190mmx89mmx42mm/7.5"x3.5"x1.7"	
Product Weight	350g/0.8lb	

MS6511

TYPE

K, J, T, E

RESOLUTION

0.1°C, 0.1°F, 0.1K

°F/°C Apo MAX MIN



MS6512

TYPE

K, J, T, E

RESOLUTION

0.1°C, 0.1°F, 0.1K

°F/°C Apo MAX MIN

