


Product SPECIFICATION SHEET



P3G-08, P3G-11, ZM2VP



Contact Type
Max Loading
Flammable Rating
Material Industrial
Conductors
Screws
Nuts
Weight

Reversed
250VAC / 3Amps
UL-94V0
Plastic PA66
Phosphorised Copper (C5191)
3 x 7 x 5.8
3mm x 5.5
70gr


ZM2VP 2 Pole Relay Base



Screw terminal socket designed for use with D Series miniature plug-in relays (model D2N & D4N). Mounting can be arranged either directly on panel or via a DIN-46377 Omega rail. Equipped with top quality fitted with large IP20 finger-protected rising clamps. Screwdriver DIN release tab and clip-on identification tab supplied as standard. Accepting also a complete series of dedicated plug-in indication and/or protection modules.

Specification

Rating		10A - 250V AC
Insulating resistance		> 1,000 Mohm
Dielectric strength		2 KV AC
Temperature range		- 40... + 70°C
Max torque		0.5 Nm
Max wiring section		2x1.5 sq.mm (2x16 AWG)
Dimensions		68x30x26h mm
Connections material		nickel plated brass
Body plastic		Self-extinguishing PA66
Self extinguishing classification	(UL 94)	V0
Enclosure classification	(EN 60529)	IP 20



BRANCH CONTACT DETAILS

Johannesburg 010 202 3300
Germiston 011 418 9600
Cape Town 021 510 0710
Pinetown 031 700 4215
Riverhorse 031 492 4800

NATIONAL CALL CENTRE

Sales 010 202 3400
Technical 010 202 3500

www.acdc.co.za