

PVT-6P, PVT-10P



Articolo Item	B204S	B206S
Sezione certificata Certified section	2.5 mm ²	4 mm ²
Tensione nominale Rated voltage	250 V	250 V
Corrente nominale Rated current	24 A	32 A
Grado di protezione Protection degree	IP 20	IP 20
Conduttori connettibili * Connectable cables *	2 x 2.5mm ²	2 x 4mm ²
Vite Screw	M3.0	M3.0
Certificazioni Approval	Ⓜ CE	Ⓜ CE
	A: 95 mm B: 16.3 mm C: 15 mm D: 6 mm E: 2.9 mm F: 2.8 mm	A: 117 mm B: 20.2 mm C: 16.6 mm D: 10 mm E: 3.4 mm F: 3.4 mm



Plug-in terminal

Utilized materials: screws of zinc plated steel, nickel plated brass insert and shell of polyamide
Working temperature from -30 to +110°C - Heat resistance + 150°C

BRANCH CONTACT DETAILS

Johannesburg 010 202 3300
 Germiston 011 418 9600
 Cape Town 021 510 0710
 Pinetown 031 700 4215
 Riverhorse 031 492 4800

NATIONAL CALL CENTRE

Sales 010 202 3400
 Technical 010 202 3500
www.acdc.co.za