

Product SPECIFICATION SHEET

SNP - Box Type Switch Mode Power Supplies



- Built-in EMI Filter
- Tested at 100% load
- Full range input voltage
- Accurate and stable output voltage
- Over-voltage protected
- Over-current protected
- Short circuit protected
- Output low ripple and noise
- working life \pm 50,000 hours

Electrical Parameters

Input Specifications	Supply Voltage Frequency Surge	90 - 264VAC 47 - 63Hz 20A@120VAC / 40A@230VAC
Output Specifications	Output voltage Adj Start time Retain time Voltage Regulation	\pm 10% \leq 1sec (input 230VAC) \geq 20ms (input 230VAC) \leq 0.5% full load
Protection	Overload Over-voltage Input-Output Insulation Input-Ground Insulation	105 - 150% Rated power, automatic recovery 105 - 150% Rated voltage 1500VAC/1min 1500VAC/1min
General Specifications	Working Temperature Storage Temperature Height above Sea level Cooling	-20°C - 60°C / 20% - 90% RH -40°C - 85°C / 10% - 95% RH \leq 2000m Natural air flow

Code	O/P Volts	O/P Amps	Ripple	Efficiency	Size LxWxH(mm)
SNP-15W/5	5VDC	3A	50mV	76%	70 x 39 x 31
SNP-25W/5		5A	50mV	76%	76 x 58 x 38
SNP-60W/5		10A	50mV	76%	129 x 98 x 38
SNP-100W/5		20A	50mV	76%	199 x 98 x 38
SNP-25W/1	12VDC	1.7A	100mV	80%	78 x 48 x 31
SNP-40W/12		3.5A	100mV	80%	160 x 98 x 42
SNP-60W/12		5A	100mV	80%	160 x 98 x 42
SNP-100W/12		8.5A	100mV	80%	130 X 98 X 40
SNP-120W/12		10A	100mV	80%	130 x 98 x 40
SNP-150W/12		12.5A	100mV	80%	160 x 98 x 50
SNP-200W/12		16.5A	100mV	80%	160 x 98 x 50
SNP-250W/12		20A	100mV	80%	200 x 110 x 50
SNP-350W/12		30A	100mV	80%	215 x 115 x 52
SNP-25W/2	24VDC	1A	100mV	80%	78 x 48 x 31
SNP-40W/24		1.8A	100mV	80%	110 x 78 x 36
SNP-60W/24		2.5A	100mV	80%	110 x 78 x 36
SNP-100W/24		4.5A	100mV	80%	130 x 98 x 40
SNP-120W/24		5A	100mV	80%	130 x 98 x 40
SNP-150W/24		6.2A	100mV	80%	160 x 98 x 50
SNP-200W/24		8.3A	100mV	80%	160 x 98 x 50
SNP-250W/24		10A	100mV	80%	200 x 110 x 50
SNP-350W/24		15A	100mV	80%	215 x 115 x 52
SNP480W/24		20A	100mV	80%	240 x 125 x 65
SNP-60W/48	48VDC	1.25A	240mV	82%	110 x 78 x 36
SNP-120W/48		2.5A	240mV	82%	130 x 98 x 40
SNP-200W/48		4.2A	240mV	82%	160 x 98 x 50
SNP-250W/48		5.2A	240mV	82%	210 x 115 x 52
SNP-350W/48		7.5A	240mV	82%	215 x 115 x 52

BRANCH CONTACT DETAILS

Johannesburg	010 202 3300
Germiston	011 418 9600
Cape Town	021 510 0710
Pinetown	031 700 4215
Riverhorse	031 492 4800

NATIONAL CALL CENTRE

Sales 010 202 3400
Technical 010 202 3500

www.acdc.co.za