
Lithium Iron Phosphate (LiFePO4) Battery

SPF12-10 LFP10-12 (12.8V10Ah)

Features of LiFePO4 Battery


- **Longer Cycle Life:** Offers up to 20 times longer cycle life and five times longer float/calendar life than lead acid battery, helping to minimize replacement cost and reduce total cost of ownership.
- **Lighter Weight:** About 40% of the weight of a comparable lead acid battery. A 'drop in' replacement for lead acid batteries.
- **Higher Power**: Delivers twice power of lead acid battery, even high discharge rate, while maintaining high energy capacity.
- **Wider Temperature Range**: -20℃~60℃.
- **Superior Safety:** Lithium Iron Phosphate chemistry eliminates the risk of explosion or combustion due to high impact, overcharging or short circuit situation.
- **Increased Flexibility:** Modular design enables deployment of up to four batteries in series and up to ten batteries in parallel.



Application

- Electric vehicles, electric mobility
- Solar/wind energy storage system
- UPS, backup power
- Telecommunication
- Medical equipment
- Lighting

Cycle Life Curve



Specification

Electrical Characteristics	Nominal Voltage	12.8V
	Nominal Capacity	10Ah (C_5,25℃)
	Energy	128Wh
	Internal Resistance	≤100mΩ
	Cycle Life	>2500 cycles @0.5C 80% DOD
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.5C
	Efficiency of Discharge	96~99% @1C
Standard Charge	Charge Voltage	14.6±0.2V
	Charge Mode	0.2C to14.6V, then14.6,charge current0.02C(CC/CV)
	Charger Current	15A
	Max. Charge Current	15A
	Charge Cut-off Voltage	14.8V±0.2V
Standard Discharge	Continuous Current	15A
	Max. Pulse Current	45A(<3s)
	Discharge Cut-off Voltage	10V
Environmental	Charge Temperature	0 °C to45 °C (32F to113F)
	Discharge Temperature	-20 °C to60 °C (-4F to140F)
	Storage Temperature	0 °C to40 °C (32F to104F)
	Water Dust Resistance	
Mechanical	Cell & Method	3.2V 5AH-4S2P
	Plastic Case	ABS
	Dimensions (in./mm.)	152*98*98mm
	Weight (lbs./kg.)	1.3KG
	Terminal	F2
	Protocol (optional)	NO
	BMS	4S15A