Product SPECIFICATION SHEET

ACDC DYNAMICS
www.acdc.co.za

SUPRA R3

Protection

- ✓ Over-load
- ✓ Under-load
- ✓ Over voltage
- ✓ Under voltage
- ✓ Phase failure
- ✓ Phase sequence changes
- ✓ Phase imbalance
- ✓ Frequent start protection

Technical specifications

- Motor voltage three phase 400V, 525V
- Motor range 0.37kW to 37kW
- Supply frequency range: 80Hz to 70Hz
- Relay contacts rating: 400V, 8A
- COS Phi range: 0.2 to 1 inductive
- Temperature range: -15°C to 70°C
- Weight: 296g

Features

- ➢ Built-in Wi-Fi
- ➢ Free basic status reporting via Website
- ➢ Up to 8 scheduler timers that work offline too
- ➢ Remote ON/OFF via Website
- ➢ Underload recovery timer
- ➢ Auxiliary inhibit
- ➢ Real-time clock
- ➢ Reset input
- ➢ Alarm relay

BRANCH CONTACT DETAILS

Johannesburg	010 202 3300
Germiston	011 418 9600
Cape Town	021 510 0710
Pinetown	031 700 4215
Riverhorse	031 492 4800

NATIONAL CALL CENTRE
Sales 010 202 3400
Technical 010 202 3500
www.acdc.co.za