ONLINE CERTIFICATIONS DIRECTORY

NLDX.E169292
Motor Controllers, Magnetic

Page Bottom

Motor Controllers, Magnetic

See General Information for Motor Controllers, Magnetic

C&S ELECTRIC LTD E169292
C-58
PHASE II
NOIDA, UP 201305 INDIA

Capacitor switching contactors , Type TC1D followed by 10, 12, 16, 20, 25, 33, 40 or 60, followed by K11 or K02 (up to 30 A) and K12 for 40A to 77A, may be followed by voltage of control circuit coil, followed by 5 (for 50 Hz), 6 (for 60 Hz) & 7 (for 50/60 Hz).

Contactors, Type LC1-D followed by 09, 12, 17, 25, 32, 40, 50, 63 or 80, followed by 3 or 9, 0 or 8 (for 25 only), may be followed by A60.

Type TC1D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01 or 10 (up to 32 A) and 11 for 40A to 95A, followed by voltage of control circuit coil followed by 5 (for 50 Hz), 6 (for 60 Hz) or 7 (for 50/60 Hz).

Type TC1D followed by 09, 12, 25, 40, 50, 65, 80 or 95 may be followed by 004 (for 4 NO Power contacts) or 008 (for 2NO and 2NC Power contacts).

Type TC followed by 4A3, 5A3, 7A3, 11A3, 15A3, 18A3, 22A3, 30A3, 37A3 45A3; followed by 01T or 10T (up to TC22A3) and 11M for 30A3, 37A3 and 45A3; followed by voltage of control circuit coil followed by 5 (for 50 Hz), 6 (for 60 Hz) or 7 (for 50/60 Hz).

Type TP1D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01 or 10 (up to 32 A) and 11 for 40A to 95A, followed by voltage of control circuit coil.

Type TP1D, followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, may be followed by 004 (for 4 NO Power contacts) or 008 (for 2NO and 2NC Power contacts).

Types LC1F, LC1FDP followed by 330A, 400A, 115A, 265A, 500A, 630A, 800A, 150A, 185A, 225A.

Definite purpose controllers intended for use in air conditioning and refrigeration equipment, Cat. Nos.TCDP202, TCDP302, TCDP402.

Cat. Nos. TCDP203, TCDP251, TCDP251S, TCDP253, TCDP301, TCDP301S, TCDP303, TCDP401, TCDP401S, TCDP403.

Reversing contactors, Type TP1D followed by C followed by 09, 12 or 25.

Type TC2D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01, 10 or 11, followed by coil voltage.

Type TP2D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01, 10 or 11, followed by coil voltage.

Reversing starters, Type TE2D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 36, followed by coil voltage, followed by Coil frequency, may be followed by Relay code 301 to 365.

Starters, Type BE1-D or LE1-D followed by 12, 25 or 32, followed by 3, followed by 5 (BE1-D only), with suffix letter, followed by three suffix numbers.

Type BE1D followed by 09, 12, 18, 32, 40, 50, 65 or 80, followed by 3, followed by 5, with suffix letter, followed by three suffix numbers; Type LE1D followed by 09, 12, 18 or 25, followed by 3, with suffix letter, followed by three suffix numbers.

Type TE1D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 36, followed by coil voltage, followed by Coil frequency, may be followed by Relay code 301 to 365.

Thermal overload relay, Model No. TR2D followed by 09301, 09302, 09303, 09304, 09305, 09306, 093x6, 09307, 09308, 09310, 09312, 09314, 12316, 18321, 25322, 32353 or 32355.

Last Updated on 2011-02-24

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



ONLINE CERTIFICATIONS DIRECTORY

NLDX2.E169292
Motor Controllers, Magnetic - Component

Page Bottom

Motor Controllers, Magnetic - Component

See General Information for Motor Controllers, Magnetic - Component

C&S ELECTRIC LTD E169292
C-58
PHASE II
NOIDA, UP 201305 INDIA

Definite purpose contactor, TCDP Series Definite Purpose AC contactors. TCDP followed by 20, 25, 30, 40, 50, 60, 75 or 90, may be followed by 1, 2, 3 or 4, may be followed by B7, G7, U7 or W7.

Marking: Company name and model designation.
Last Updated on 2009-12-28

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



ONLINE CERTIFICATIONS DIRECTORY

NLDX7.E169292
Motor Controllers, Magnetic Certified for Canada

Page Bottom

Motor Controllers, Magnetic Certified for Canada

See General Information for Motor Controllers, Magnetic Certified for Canada

C&S ELECTRIC LTD E169292
C-58
PHASE II
NOIDA, UP 201305 INDIA

Capacitor switching contactors, Type TC1D followed by 10, 12, 16, 20, 25, 33, 40 or 60, followed by K11 or K02 (up to 30 A) and K12 for 40A to 77A, may be followed by voltage of control circuit coil, followed by 5 (for 50 Hz), 6 (for 60 Hz) & 7 (for 50/60 Hz).

Contactors, Type LC1-D followed by 09, 12, 17, 25, 32, 40, 50, 63 or 80, followed by 3 or 9, 0 or 8 (for 25 only), may be followed by A60.

Type TC1D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01 or 10 (up to 32 A) and 11 for 40A to 95A, followed by voltage of control circuit coil followed by 5 (for 50 Hz), 6 (for 60 Hz) or 7 (for 50/60 Hz).

Type TC1D followed by 09, 12, 25, 40, 50, 65, 80 or 95 may be followed by 004 (for 4 NO Power contacts) or 008 (for 2NO and 2NC Power contacts).

Type TC followed by 4A3, 5A3, 7A3, 11A3, 15A3, 18A3, 22A3, 30A3, 37A3 45A3; followed by 01T or 10T (up to TC22A3) and 11M for 30A3, 37A3 and 45A3; followed by voltage of control circuit coil followed by 5 (for 50 Hz), 6 (for 60 Hz) or 7 (for 50/60 Hz).

Type TP1D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01 or 10 (up to 32 A) and 11 for 40A to 95A, followed by voltage of control circuit coil.

Type TP1D, followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, may be followed by 004 (for 4 NO Power contacts) or 008 (for 2NO and 2NC Power contacts).

Types LC1F, LC1FDP followed by 330A, 400A, 115A, 265A, 500A, 630A, 800A, 150A, 185A, 225A.

Definite purpose controllers intended for use in air conditioning and refrigeration equipment, Cat. Nos.TCDP202, TCDP302, TCDP402.

Cat. Nos. TCDP203, TCDP251, TCDP251S, TCDP253, TCDP301, TCDP301S, TCDP303, TCDP401, TCDP401S, TCDP403.

Reversing contactors, Type TP1D followed by C followed by 09, 12 or 25.

Type TC2D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01, 10 or 11, followed by coil voltage.

Type TP2D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 01, 10 or 11, followed by coil voltage.

Reversing starter, Type TE2D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95; followed by 36; followed by coil voltage, followed by Coil frequency, may be followed by Relay code 301 to 365.

Starters, Type BE1-D or LE1-D followed by 12, 25 or 32, followed by 3, followed by 5 (BE1-D only), with suffix letter, followed by three suffix numbers.

Type BE1D followed by 09, 12, 18, 32, 40, 50, 65 or 80, followed by 3, followed by 5, with suffix letter, followed by three suffix numbers; Type LE1D followed by 09, 12, 18 or 25, followed by 3, with suffix letter, followed by three suffix numbers.

Type TE1D followed by 09, 12, 18, 25, 32, 40, 50, 65, 80 or 95, followed by 36, followed by coil voltage, followed by Coil

frequency, may be followed by Relay code 301 to 365.

Thermal overload relay, Model No. TR2D followed by 09301, 09302, 09303, 09304, 09305, 09306, 093x6, 09307, 09308, 09310, 09312, 09314, 12316, 18321, 25322, 32353, 32355.

Last Updated on 2011-02-24

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



ONLINE CERTIFICATIONS DIRECTORY

NLDX8.E169292
Motor Controllers, Magnetic Certified for Canada - Component

Page Bottom

Motor Controllers, Magnetic Certified for Canada - Component

See General Information for Motor Controllers, Magnetic Certified for Canada - Component

C&S ELECTRIC LTD E169292
C-58
PHASE II
NOIDA, UP 201305 INDIA

Definite purpose contactor, TCDP Series Definite Purpose AC contactors. TCDP followed by 20, 25, 30, 40, 50, 60, 75 or 90, may be followed by 1, 2, 3 or 4, may be followed by B7, G7, U7 or W7.

Marking: Company name, model designation, and the Recognized Component Mark for Canada, c UL us

Last Updated on 2009-12-28

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

ONLINE CERTIFICATIONS DIRECTORY

NKCR.E171526
Auxiliary Devices

Page Bottom

Auxiliary Devices

See General Information for Auxiliary Devices

C&S ELECTRIC LTD E171526
C-58
PHASE II
NOIDA, UP 201305 INDIA

Auxiliary contactor, Cat No. TCA2DN followed by 31, 40, 22, followed by voltage of control circuit coil, followed by 5 (for 50 Hz), 6 (for 60 Hz) or 7 (for 50/60 Hz).

Auxiliary power block, Cat. No. TA1DN followed by 31, 22, 40, 13, 04, 02, 20, 11, 10 or 01.

Auxiliary contact blocks, Cat No. TA8DN followed by 11 or 20.

Cat. No. TA8DP followed by 11.

Thermal overload relays, Cat No. LR1-D or TR1-D followed by 09, 12, 16, 25, 32, 40, 63 and 80, may be followed by additional numbers, may be followed by R, may be followed by A65.

Model TR2D followed by 09301, 09302, 09303, 09304, 09305, 09306, 093x6, 09307, 09308, 09310, 09312, 09314, 12316, 18321, 25322, 32353, 32355, 40353, 40355, 65357, 65359, 65361, 80363 and 95365. Rating: B600 (600Vac max, 360VA) Relay Class designation 10

Thermal overload relays - current transformer operated, Series LR1F, Types LR1F105, LR1F125, LR1F160, LR1F200, LR1F250, LR1F315, LR1F400, LR1F500, LR1F630. Rating: B600 (600Vac max, 360VA) Relay Class designation 10.

Pneumatic time delay auxiliary contact blocks, Series TA2D followed by T0, T2, S2 and T4.

Series TA3D followed by R0, R2 and R4.

Mounting kit for thermal overload relays, Series TA7D followed by 0964, 3264 and 4064.

Mechanical interlock kit, Series LA9D followed by 09978, 50978 or 80978.

Add-on jogging contact, LA9D09906J.

NO block contact, LA9D09906.

Add On block, mechanical latch block with manual or electrical delatch, LA6DK01 followed by control circuit coil voltage.

Last Updated on 2010-04-16

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



ONLINE CERTIFICATIONS DIRECTORY

NKCR2.E171526
Auxiliary Devices - Component

Page Bottom

Auxiliary Devices - Component

See General Information for Auxiliary Devices - Component

C&S ELECTRIC LTD E171526
C-58
PHASE II
NOIDA, UP 201305 INDIA

Auxiliary devices, pilot light, Model No. RCB7-IVL7 may be followed by 1 or 3 or 4 or 5 or 6 or 7 or 8 and X. .

Marking: Company name, catalog designation and electrical rating.
Last Updated on 2008-04-10

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



ONLINE CERTIFICATIONS DIRECTORY

NKCR7.E171526
Auxiliary Devices Certified for Canada

Page Bottom

Auxiliary Devices Certified for Canada

See General Information for Auxiliary Devices Certified for Canada

C&S ELECTRIC LTD E171526
C-58
PHASE II
NOIDA, UP 201305 INDIA

Auxiliary contactor, Cat No. TCA2DN followed by 31, 40, 22, followed by voltage of control circuit coil, followed by 5 (for 50 Hz), 6 (for 60 Hz) or 7 (for 50/60 Hz).

Auxiliary power block, Cat. No. TA1DN followed by 31, 22, 40, 13, 04, 02, 20, 11, 10 or 01.

Auxiliary contact blocks, Cat No. TA8DN followed by 11 or 20.

Cat. No. TA8DP followed by 11.

Thermal overload relays, Cat No. LR1-D or TR1-D followed by 09, 12, 16, 25, 32, 40, 63 and 80, may be followed by additional numbers, may be followed by R, may be followed by A65.

Model TR2D followed by 09301, 09302, 09303, 09304, 09305, 09306, 093x6, 09307, 09308, 09310, 09312, 09314, 12316, 18321, 25322, 32353, 32355, 40353, 40355, 65357, 65359, 65361, 80363 and 95365. Rating: B600 (600Vac max, 360VA) Relay Class designation 10

Thermal overload relays - current transformer operated, Series LR1F, Types LR1F105, LR1F125, LR1F160, LR1F200, LR1F250, LR1F315, LR1F400, LR1F500, LR1F630. Rating: B600 (600Vac max, 360VA) Relay Class designation 10.

Pneumatic time delay auxiliary contact blocks, Series TA2D followed by T0, T2, S2 and T4.

Series TA3D followed by R0, R2 and R4.

Mounting kit for thermal overload relays, Series TA7D followed by 0964, 3264 and 4064.

Mechanical interlock kit, Series LA9D followed by 09978, 50978 or 80978.

Add-on jogging contact, LA9D09906J.

NO block contact, LA9D09906.

Add On block, mechanical latch block with manual or electrical delatch, LA6DK01 followed by control circuit coil voltage.

Last Updated on 2010-04-16

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



ONLINE CERTIFICATIONS DIRECTORY

NKCR8.E171526
Auxiliary Devices Certified for Canada - Component

Page Bottom

Auxiliary Devices Certified for Canada - Component

See General Information for Auxiliary Devices Certified for Canada - Component

C&S ELECTRIC LTD E171526
C-58
PHASE II
NOIDA, UP 201305 INDIA

Auxiliary devices, pilot light, Model No. RCB7-IVL7 may be followed by 1 or 3 or 4 or 5 or 6 or 7 or 8 and X.

Marking: Company name, catalog designation and the Recognized Component Mark for Canada c UL us.

Last Updated on 2008-04-10

Questions? Print this page Notice of Disclaimer Page Top

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.