THB.392.A4A.R

MADE IN ITALY

TH392 - Circular mini-junction connector 4 ways type "H" IP68

KIT

IP68



GENERAL DESCRIPTION

Type of installation	Joint connector (re-usable/re-accessible)
Type of product (Family)	TEETUBE® - In-line and junction circular connectors IP68/IP69K
Product name (Series)	TH392 - Circular mini-junction connector 4 vie tipo "H" IP68
Product configuration	In-line joint connector
Type of Fixation	With quick-fix mounting clip *• Mounting clip to be ordered separately (code 6000302CC).*
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	28 mm x 54 mm x 80 mm

ELECTRICAL CHARACTERISTICS

Number of poles	4
Contact marking	1 - 2 - 3 - 4(E)
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 17.5A
Operating voltage	max. 450V AC

Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (30m,2h)
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.5 mm^2 - 4.0 mm^2 *• min. 2x4.0mm^2 / max. 4x1.5mm^2*
Wire cross-section min. - max. (Solid cable)	0.5 mm^2 - 4.0 mm^2 *• min. 2x4.0mm^2 / max. 4x1.5mm^2*
Cable diameter min. - max.	5.0 mm - 12.0 mm (main cable) / 5.0 mm - 12.0 mm (branch cable) *• Accessories e riduzioni per cavi incluse nella confezione. Closure cap included in the kit.*

MATERIAL CHARACTERISTICS

Connector housing	PA68 UL94 V0 GWT 960°
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	TPE
Grommets	TPE
Contacts	CuZn (nickel plated)
Screws	Steel (rivestimento Zinco)
Material properties	Halogen Free - Silicone Free
T marking	T 85°C
Operating temperature range	-40°C / +125°C

INSTALLATION INSTRUCTIONS

- 606004100 IST TH392 nuovo NEW PDF • 1 MB
- 606004100 IST TH392 nuovo Lungo NEW PDF • 695 KB

CERTIFICATIONS AND TEST REPORTS

- TH392 CA0205752 resinato PDF • 290 KB
- CE-TH392 DOCX • 352 KB
- TH392 CA0205251 PDF • 1 MB

MARKETING COLLATERALS

- X DRY A4 ita 2 PDF • 76 KB
- cartolina 210x105 ita 2 PDF • 82 KB
- Cameriere pag intera PDF • 2 MB
- Pannello 3 PDF • 457 KB

DRAWINGS

- THB392A4A-R4ASTEP • 10 MB • CONFIDENTIAL DOCUMENT

 © Techno s.r.l.

No responsibility is taken for the correctness of this information. All technical data or other eventual product modifications and improvements can be carried out without notice. The images are purely for information.

Proof Tracking Index (PTI)	PTI 250

Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 60998-1:2004

PACKAGING INFORMATION

Packaging method	single packed unit
Quantity (product/bag)	1 product/bag
Quantity (product/box)	30 bags/box
Unit weight	109,5 gram/bag
Box dimension	400 x 210 x 170

Accessorieses and installation instructions included in the kit.

 © Techno s.r.l.

No responsibility is taken for the correctness of this information. All technical data or other eventual product modifications and improvements can be carried out without notice. The images are purely for information.