THR.406.S5A

TH406 - Plug&Socket connector panel-mounted IP68

MADE IN ITALY

KIT

IP68



GENERAL DESCRIPTION

Type of installation	Plug and Socket connector
Type of product (Family)	TEEPLUG® - IP68 Plug&Socket circular connectors
Product name (Series)	TH406 - Plug&Socket connector panel-mounted IP68
Product configuration	Panel-mounted plug+socket connector with fixing nut *• Plug&Socket connectors included in the kit. Fixing nut and accessories included in the kit.*
Thread	Hole 28 mm
Panel thickness min. - max.	1.0 mm - 12.0 mm
Colour	Black (Plastic components) - Techno green (Rubber components)
Outer dimension	Φ 36.5 mm x 70 mm (when plug-socket matched)

ELECTRICAL CHARACTERISTICS

Number of poles	5
Contact marking	1 - 2 - E - L - N
Type of connection	screw (M3 - max. 0.5 Nm)
Operating current	max. 17.5A
Operating voltage	max. 400V AC
Impulse withstand voltage	6KV

Contact our Customer Service for availability of other markings.

MECHANICAL CHARACTERISTICS

Protection against solid/water (IP)	IP68 (10m,1h)
Protection against impact (IK)	IK08
Corrosion resistance	Salt mist, 1.000 ore, 5% salt solutions, 35°C EN60068-2-11:2000, Test Ka (168h)

Contact our Customer Service for availability of products with different IP and IK protection degrees.

CABLE CHARACTERISTICS

Wire cross-section min. - max. (Stranded cable)	0.5 mm^2 - 4.0 mm^2 *• min. 2x4.0mm^2 / max. 5x1.5mm^2*
Wire cross-section min. - max. (Solid cable)	0.5 mm^2 - 4.0 mm^2 *• min. 2x4.0mm^2 / max. 5x1.5mm^2*
Cable diameter min. - max.	6.0 mm - 14.0 mm *• Accessories e riduzioni per cavi incluse nella confezione.*

MATERIAL CHARACTERISTICS

Body	PA66 UL94 V2 GWT 850°C
Connector housing	PA66 GF UL94 V0 GWT 960°C
Cable gland	PA66 UL94 V2 GWT 850°C
Sealing	Silicone
Grommets	TPE
Contacts	CuZn (nickel plated)

INSTALLATION INSTRUCTIONS

- IST TH405-406-408-409 v01 PDF • 776 KB

CERTIFICATIONS AND TEST REPORTS

- CE-TH406 2-3-5-6 DOC • 131 KB
- TH406 CA0202680 2-3 poli PDF • 305 KB
- TH406 CA0202679 2-3-5-6 poli PDF • 327 KB
- • 273 KB

MARKETING COLLATERALS

- maggiopubblicitn PDF • 1 MB

 © Techno s.r.l.

No responsibility is taken for the correctness of this information. All technical data or other eventual product modifications and improvements can be carried out without notice. The images are purely for information.

Screws	Steel (rivestimento Zinco)
Impulse withstand category	II
Pollution degree	2
Material properties	Halogen Free - Silicone Free
T marking	T 125°C
Operating temperature range	-40°C / +125°C
Proof Tracking Index (PTI)	PTI 175

Contact our Customer Service for more information on additional tests and approvals.

INDUSTRY STANDARDS

Standard number	EN 61984:2009

PACKAGING INFORMATION

Packaging method	single packed unit
Quantity (product/bag)	1 product/bag
Quantity (product/box)	50 bags/box
Unit weight	39,6 gram/bag
Box dimension	400 x 230 x 400

Accessorieses and installation instructions included in the kit.

 © Techno s.r.l.

No responsibility is taken for the correctness of this information. All technical data or other eventual product modifications and improvements can be carried out without notice. The images are purely for information.