

Product SPECIFICATION SHEET

E27 / B22 LED LAMP 110V /230V



TP-DL




L-BL



XH-T95 E27/B22



	230 / 110V
	PF > 0.85
	RA > 70
	E27 / B22
	110°
	35 000h



ADDITIONAL INFORMATION

- Frosted lense to diffuse the light efficiently
- Last 2.5 times longer than traditional lamps
- 270° Beam Angle
- High durability

SUGGESTED APPLICATIONS



Code E27	Code B22	Code 110V	Wattage	Lumens	Size (mm)	Colour Temp.
TP-DL-5W-WW	TP-DL-5W-WW	-	5W	470-530lm	Ø50 x 99.5	2700 - 3300K
TP-DL-5W-CW	TP-DL-5W-CW	TP-DL-5W-CW 110V	5W	470-530lm	Ø50 x 99.5	4000K
TP-DL-10W-WW	TP-DL-10W-WW	-	10W	760-870lm	Ø60 x 119	2700 - 3300K
TP-DL-10W-CW	TP-DL-10W-CW	TP-DL-10W-CW 110V	10W	760-870lm	Ø60 x 119	4000K
XH-T95-20W-E27-WW	XH-T95-20W-B22-WW	-	20W	1600lm	Ø95 x 200	2700 - 3300K
XH-T95-20W-E27-CW	XH-T95-20W-B22-CW	-	20W	1600lm	Ø95 x 200	4000K
XH-T95-30W-E27-WW	XH-T95-30W-B22-WW	-	30W	2400lm	Ø95 x 200	2700 - 3300K
XH-T95-30W-E27-CW	XH-T95-30W-B22-CW	-	30W	2400lm	Ø95 x 200	4000K
XH-T110-40W-E27-WW	XH-T110-40W-B22-WW	-	40W	3200lm	Ø110 x 220	2700 - 3300K
XH-T110-40W-E27-CW	XH-T110-40W-B22-CW	-	40W	3200lm	Ø110 x 220	4000K
XH-T149-60W-E27-WW	XH-T149-60W-B22-WW	-	60W	4800lm	Ø110 x 220	2700 - 3300K
XH-T149-60W-E27-CW	XH-T149-60W-B22-CW	-	60W	4800lm	Ø110 x 220	4000K
L-BL-0490	-	-	55W	4200lm	Ø110 x 218	6000K
L-BL-0494	-	-	65W	5400lm	Ø100 x 300	6000K

BRANCH CONTACT DETAILS

Johannesburg	010 202 3300
Germiston	011 418 9600
Cape Town	021 510 0710
Pinetown	031 700 4215
Riverhorse	031 492 4800

NATIONAL CALL CENTRE

Sales	010 202 3400
Technical	010 202 3500

www.acdc.co.za