SPECIFICATION



Technical Application Guide for LED Downlight

UP-DL77-35W

ACDC DYNAMICS
www.acdc.co.za

Introduction







COB downlight is unique designed with reflector and Citizen COB high power LED chip. ADC12 die-casting aluminium profile provides excellent thermal dissipation. Adjustable lighting direction provides all possible lighting effects. Isolated driver solution both in dimmable and non-dimmable version achieves great dimming compatibility with worldwide brand dimmers.

- Up to 70% energy saving compared to standard CFL
- Long lifetime of L70 50,000 hours
- Dimmable when using triac dimmer
- 45°/60° wide beam angle
- Ø165-170mm cutout
- CCT: 4000K 5000K
- No UV/IR light
- Environment friendly, without Mercury or any other hazardous substances

Application notes

- IP20 for indoor use only
- Professional electrician for installation only
- Switch off before installation
- Do not touch when in use
- Keep away from hot steam and corrosive gas

Application Areas

It is designed for general lighting applications in office, supermarket, shop, school, hotel, etc. It is also widely used for public areas, such as stairway, lobby, reception, corridors etc.

26 Nguni Drive, Longmeadow Business Estate, Edenvale, Gauteng, South Africa
Sales: 010 202 3400 | Technical: 010 202 3500 | Johannesburg: 010 202 3300
Germiston: 011 418 9600 | Cape Town: 021 510 0710 | Pinetown: 031 700 4215 | Riverhorse: 031 492 4800

ACDC DYNAMICS
www.acdc.co.za

Product Information

5 Year Warranty





Technical Specifications

Model	Voltage	Power	Power Factor	Lumen (±5%)	Beam angle	CCT	Lifespan	CRI	Dimmable	Dimension
UP-DL77-6-35W	AC230V	35W	≥0.9	110lm/W	24°/45°/60°	4000K	50000hs	≥80	No	Ø180*128.5mm cutout Ø165-170mm
UP-DL77-6-35W	AC230V	35W	≥0.9	110lm/W	24°/45°/60°	5000K	50000h	≥80	No	Ø180*128.5mm cutout Ø165-170mm

Driver data Sheet

Driver data	Non dim
Input rated Voltage	AC230V
Frequency	50Hz
Input Voltage	AC200-240V
Efficiency	≥84%
Total load Wattage	35W±5%
Power Factor	≥0.9
Rated input current	≤0.2A
Full load output Voltage	DC25-42V
Rated output current	800mA
Output current range	800mA±5%
Power tolerance	±5%
Current output tolerance	±5%
Dimming range	—
Dimmer	—
THD	<18%
Short circuit protection	PASS
Over voltage protection	PASS
Over temperature protection	PASS
Withstand voltage	AC3750V

Fixture Compatibility

Rated Wattage	Electrical Classification	Ingress Protection	Operating Temp	Operating Humidity	Storage Temp
35W	II	IP20	-20°C~45°C	0~90%	-20°C~65°C

26 Nguni Drive, Longmeadow Business Estate, Edenvale, Gauteng, South Africa
Sales: 010 202 3400 | Technical: 010 202 3500 | Johannesburg: 010 202 3300
Germiston: 011 418 9600 | Cape Town: 021 510 0710 | Pinetown: 031 700 4215 | Riverhorse: 031 492 4800

ACDC DYNAMICS
www.acdc.co.za

Spectral Distribution

4000K



5000K



Photometric Diagram

4000K



5000K



26 Nguni Drive, Longmeadow Business Estate, Edenvale, Gauteng, South Africa
Sales: 010 202 3400 | Technical: 010 202 3500 | Johannesburg: 010 202 3300
Germiston: 011 418 9600 | Cape Town: 021 510 0710 | Pinetown: 031 700 4215 | Riverhorse: 031 492 4800

ACDC DYNAMICS
www.acdc.co.za

Polar Diagram Comparison



AVERAGE BEAM ANGLE (50%): 65.4DEG

UNIT: cd

- C0/180, 66.3 deg
- C30/210, 66.3 deg
- C60/240, 65.1 deg
- C90/270, 63.8 deg



Driver lifetime & LED light decay rate





Temperature

- The testing is operated at 25°C
- The highest withstand temperature of IC, MOS could be 120°C
- The highest withstand temperature of LED junction temperature is 150°C





The driver lifespan is based on capacitor working temperature.

26 Nguni Drive, Longmeadow Business Estate, Edenvale, Gauteng, South Africa
Sales: 010 202 3400 | Technical: 010 202 3500 | Johannesburg: 010 202 3300
Germiston: 011 418 9600 | Cape Town: 021 510 0710 | Pinetown: 031 700 4215 | Riverhorse: 031 492 4800

ACDC DYNAMICS
www.acdc.co.za

Installation

Install requirements	
A-gap above the fitting	25mm
B-gap to the building material	25mm
C-gap to the thermal insulation	25mm



Ceiling Opening



1

Connect Power supply



2

A. Hold back spring clips



B. Push downlight into position

3



4

Packaging Information

	SIZE(CM)	N.W/pc (KGS)	G.W.(KGS)	Q'TY(PCS)
Carton	61.5*41.5*32	1.07	16	12

	CTNS	Q'TY(PCS)	VOLUME(CBM)
20" standard container	338	4056	28
40" standard container	676	8112	56



26 Nguni Drive, Longmeadow Business Estate, Edenvale, Gauteng, South Africa
Sales: 010 202 3400 | Technical: 010 202 3500 | Johannesburg: 010 202 3300
Germiston: 011 418 9600 | Cape Town: 021 510 0710 | Pinetown: 031 700 4215 | Riverhorse: 031 492 4800

ACDC DYNAMICS
www.acdc.co.za