

Product SPECIFICATION SHEET




ZMD Series Base





Screw terminal socket designed for use with D Series miniature plug-in relays (model D2N & D4N). Panel mounting can be arranged either directly or via a DIN-46377 Omega rail. Its screw terminals are fitted with jaw-type IP20 finger-protected rising clamps and the reduced lateral dimension is ideally suited for high-density DIN-Rail applications. Clip-on identification tab supplied as standard, while an optional plastic retaining clip, acting also as a relay ejecting device, is available on request. Accepting also a complete series of dedicated plug-in indication and/or protection modules.

Specification


Rating	(2 pole)	12A - 300V AC
	(4 pole)	6A - 300V AC
Insulating resistance		> 1,000 Mohm
Dielectric strength		2 KV AC
Dimensions		76x27x43 mm
Cennect ZMD4 - four pole		nickel plated brass
Body plastic		glass-filled PA6
Self extinguishing classification	(UL 94)	V2
Protection Rating	(EN 60529)	IP 20



ZMD4 - four pole



ZMD2 - two pole



ZMD2 - two pole

BRANCH CONTACT DETAILS

Johannesburg 010 202 3300
Germiston 011 418 9600
Cape Town 021 510 0710
Pinetown 031 700 4215
Riverhorse 031 492 4800

NATIONAL CALL CENTRE

Sales 010 202 3400
Technical 010 202 3500

www.acdc.co.za